


PRODUCT SPECIFICATION

COSMO ELECTRONICS CO., LTD.	PHOTO MOS RELAYS: KAQV210	SHEET 1 OF 7
---------------------------------------	-------------------------------------	--------------

- OUTSIDE DIMENSION :



- Turn on/Turn off time



Absolute Maximum Ratings ($T_A=25^\circ C$)

Emitter (Input)

Reverse Voltage	5.0V
Continuous Forward Current	50mA
Peak Forward Current (1s)	1A
Power Dissipation.	100mW
Derate Linearly from 25. C	1.3mW/. C

Detector (Output)

Output Breakdown Voltage	+350V
Continous Load Current	+130mA
Power Dissipation	500mW

General Characteristics

Isolation Test Voltage.	3750VAC _{RMS}
Isolation Resistance	
$V_{IO} = 500V, T_A = 25^\circ C$	$\geq 10^{10} \Omega$
Total Power Dissipation	550mW

Derate Linearly form 25. C	2.5mW/. C
Storage Temperature Range	-40 to +150. C
Operating Temperature Range.	-40 to +85. C
Junction Temperature	100. C
Soldering Temperature, 2mm from case, 10 sec.	260. C








PRODUCT SPECIFICATION

COSMO ELECTRONICS CO., LTD.	PHOTO MOS RELAYS: KAQV210	SHEET 2 OF 7
---------------------------------------	-------------------------------------	--------------

Characteristics

($T_A = 25^\circ C$)

Description		Symbol	Min.	Typ.	Max.	Unit	Test Condition
Emitter (Input)							
Forward Voltage	V_F			1.8	2.0	V	$I_F = 10mA$
Operation Input Current	I_{FON}				5	mA	$V_L = \pm 20V, I_L = 100mA, t = 10 ms$
Recovery Input Current	I_{FOFF}	0.2				mA	$V_L = \pm 20V, I_L = < 5\mu A$
Dectorctor (Output)							
Output Breakdown Voltage	V_B	350				V	$I_B = 50\mu A$
Output Off-State Leakage	I_{TOFF}		0.2	1		μA	$V_T = 100V, I_F = 0mA$
I/O Capacitance	C_{ISO}		6			pF	$I_F = 0, f = 1MHz$
ON Resistance	Connection	A		20	30	Ω	$I_L = 100mA, I_F = 10mA$
		B	R_{ON}	10	15		
		C		5	7.5		
Turn-on Time	T_{ON}			0.3	1.0	ms	$I_F = 10mA, V_L = \pm 20V$ $t = 10ms, I_L = \pm 100mA$
Turn-off Time	T_{OFF}			0.7	1.5	ms	


Mos Relay Schematic and Wiring Diagrams							
Type	Schematic	Output configuration	Load	Con-nection	Wiring diagram		
KAQV210	 	1a	AC/DC	A			
							
							

PRODUCT SPECIFICATION


COSMO ELECTRONICS CO., LTD.	PHOTO MOS RELAYS: KAQV210	SHEET 3 OF 7
---------------------------------------	-------------------------------------	--------------

DATA CURVE


Load current vs. ambient temperature
 Allowable ambient temperature:
 -40°C to 85°C




On resistance vs. ambient temperature
 Across terminals 4 and 6 pin
 LED current: 5mA
 Continuous load current: 130 mA(DC)



Turn on time vs. ambient temperature
 Load voltage 350 V(DC)
 LED current : 5mA
 Continuous load current: 130mA(DC)



Turn off time vs. ambient temperature
 LED current: 5mA; Load voltage: 350V(DC)
 Continuous load current: 130mA(DC)




PRODUCT SPECIFICATION

COSMO ELECTRONICS CO., LTD.	PHOTO MOS RELAYS: KAQV210	SHEET 4 OF 7
---------------------------------------	-------------------------------------	--------------


LED operate vs. ambient temperature
Load voltage: 350V(DC)

Continuous load current: 130mA(DC)




LED turn off current vs. ambient temperature
Load voltage: 350V(DC)

Continuous load current: 130mA(DC)



LED dropout voltage vs. ambient temperature


LED current: 5 to 50mA



Voltage vs. current characteristics of output at MOS FET portion

Measured portion: across terminals 4 and 6 pin


Ambient temperature: 25°C




PRODUCT SPECIFICATION

COSMO ELECTRONICS CO., LTD.	PHOTO MOS RELAYS: KAQV210	SHEET 5 OF 7
---------------------------------------	-------------------------------------	--------------


LED forward current vs. turn on time
Across terminals 4 and 6pin; Load voltage: 350V(DC); Continuous load current: 130mA(DC); Ambient temperature: 25° C




Off state leakage current
Across terminals 4 and 6pin
Ambient temperature: 25° C



LED forward current vs. turn off time
Across terminals 4 and 6pin; Load voltage: 350V(DC); Continuous load current: 130 mA(DC); Ambient temperature: 25° C



Applied voltage vs. output capacitance
Across terminals 4 and 6pin
Frequency: 1MHz; Ambient temperature: 25° C



PRODUCT SPECIFICATION


COSMO
ELECTRONICS CO., LTD.

PHOTO MOS RELAYS:
KAQV210

SHEET 6 OF 7


USING METHODS

Examples of resistance value to control LED forward current I_F



E	R
3.3V	Approx. 240 ohm
5V	Approx. 540 ohm
12V	Approx. 1.8K ohm
15V	Approx. 2.4K ohm
24V	Approx. 4K ohm

- (1) LED forward current must be more than 5mA, at E min.
- (2) LED forward current must be less than 50mA, at E max.



PRODUCT SPECIFICATION



COSMO
ELECTRONICS CO., LTD.

PHOTO MOS RELAYS:
KAQV210

SHEET 7 OF 7

USING METHODS

Regulate the spike voltage generated on the inductive load as follows



R-C Snubber