

Descriptions

The S1117A and S1117 series of positive adjustable and fixed regulators are designed to provide 1A with higher efficiency than currently available devices. All internal circuitry is designed to operate down to 1.3V input to output differential. On-Chip trimming adjusts reference Voltage to 2%

Features

- Output Current of 1A
- 1.3V Maximum Dropout voltage at 1A Output Current
- 100% Thermal Limit Burn-In
- Fast Transient Response


Ordering Information

Type NO.	Marking	Package Code
S1117AD/S1117xxD	S1117□□D	D-PAK

□□: Voltage Code (Aj : 1.25V, 15:1.5V, 18: 1.8V, 25:2.5V, 285:2.85V, 33:3.3V, 50:5.0V)

Outline Dimensions

unit : mm



PIN Connections

1. GND/ADJ
2. Output
3. Input

S1117AD/S1117-xxD

Absolute Maximum Ratings

Ta=25°C

Characteristic	Symbol	Ratings	Unit
Operating Input voltage	V _{IN}	V _{out} = 1.25, 1.5, 1.8	16
		V _{out} = 2.5 2.8 3.3 5.0	20
Power Dissipation (without Heatsink)	P _D	1.3	W
Lead Temperature (Soldering, 10 sec)	T _{LEAD}	300	°C
Operating Junction Temperature	T _J	-30 ~ 125	°C
Storage Temperature	T _{STG}	-55 ~ 150	°C

Device Selection Guide (NOTE1)

Device	Output Voltage
S1117A	Adj
S1117-1.5	1.5V
S1117-1.8	1.8V
S1117-2.5	2.5V
S1117-2.85	2.85V
S1117-3.3	3.3V
S1117-5.0	5V

Note 1 : Other Fixed Versions are available Vout=1.5V to 5V

Electrical Characteristics

(Electrical Characteristics at T_J = 25°C and I_{Load}=10mA unless otherwise specified.)

Characteristic	Symbol	Device	Test Condition	Min	Typ	Max	Unit
Output Voltage	V _{OUT}	S1117A	V _{IN} = (V _{out} +1.5V), I _{OUT} = 10mA	1.238	1.25	1.262	V
			V _{IN} = (V _{out} +1.5V) to 12V I _{OUT} = 0 to 1000mA	*		1.225	
		S1117-15	V _{IN} = (V _{out} +1.5V), I _{OUT} = 10mA	1.47	1.5	1.53	
			V _{IN} = (V _{out} +1.5V) to 12V I _{OUT} = 0 to 1000mA	*		1.44	
		S1117-18	V _{IN} = (V _{out} +1.5V), I _{OUT} = 10mA	1.764	1.8	1.836	
			V _{IN} = (V _{out} +1.5V) to 12V I _{OUT} = 0 to 1000mA	*		1.728	
		S1117-25	V _{IN} = (V _{out} +1.5V), I _{OUT} = 10mA	2.45	2.5	2.55	
			V _{IN} = (V _{out} +1.5V) to 12V I _{OUT} = 0 to 1000mA	*		2.4	
		S1117-285	V _{IN} = (V _{out} +1.5V), I _{OUT} = 10mA	2.793	2.85	2.907	
			V _{IN} = (V _{out} +1.5V) to 12V I _{OUT} = 0 to 1000mA	*		2.736	

Electrical Characteristics (Continued)

(Electrical Characteristics at $T_j = 25^\circ\text{C}$ and $I_{\text{LOAD}}=10\text{mA}$ unless otherwise specified.)

Characteristic	Symbol	Device	Test Condition	Min	Typ	Max	Unit	
Output Voltage	V_{OUT}	S1117-33	$V_{\text{IN}} = (V_{\text{out}}+1.5\text{V}), I_{\text{OUT}} = 10\text{mA}$	3.234	3.3	3.366	V	
			$V_{\text{IN}} = (V_{\text{out}}+1.5\text{V})$ to 12V $I_{\text{OUT}} = 0$ to 1000mA	*		3.168		3.432
		S1117-50	$V_{\text{IN}} = (V_{\text{out}}+1.5\text{V}), I_{\text{OUT}} = 10\text{mA}$	4.9	5.0	5.1		
			$V_{\text{IN}} = (V_{\text{out}}+1.5\text{V})$ to 12V $I_{\text{OUT}} = 0$ to 1000mA	*		4.8		5.2
Line Regulation Note1	ΔV_{OUT}	All	$(V_{\text{out}}+1.5\text{V}) \leq V_{\text{IN}} \leq 12\text{V}$ $I_{\text{OUT}}=10\text{mA}$	*	-	10	30	mV
Load Regulation Note1	ΔV_{OUT}	All	$(V_{\text{IN}} - V_{\text{out}})=2\text{V}, 10\text{mA} \leq I_{\text{OUT}} \leq 1\text{A}$	*	-	10	30	mV
Quiescent Current	I_{Q}	All Fixed Versions	$V_{\text{IN}}= 11.5\text{V}, I_{\text{OUT}}=0\text{mA}$	*	-	3.6	10	mA
Minimum Load Current	I_{LMIN}	S1117A	$V_{\text{IN}}=(V_{\text{OUT}}+1.5), V_{\text{OUT}}=0\text{V}$	*		3	7	mA
Adjust Pin Current	I_{ADJ}	S1117A	$V_{\text{IN}} = (V_{\text{out}}+1.5\text{V})$ to 12V $I_{\text{OUT}} = 10\text{mA}$	*		55	90	μA
Dropout Voltage Note3	V_{D}	All	$I_{\text{OUT}} = 1000\text{mA}$	*	-	1.2	1.3	V
Ripple Rejection Note2	RR	All	$V_{\text{IN}}-V_{\text{OUT}}=1.5\text{V}, f=120\text{Hz}$ $I_{\text{OUT}}=1000\text{mA}, V_{\text{RIPPLE}}=1\text{V}_{\text{P-P}}$		60	72	-	dB
Output Noise Voltage	eN	All	$f=10$ to 10KHz		-	100	-	μV
Output Current	I_{OUT}	All	$(V_{\text{IN}}-V_{\text{OUT}})=1.5\text{V}$	*	1	1.5		A

The * denotes the specifications which apply over the full temperature range.

Note 1: Low duty pulse testing with Kelvin connections required.

Note 2: 120Hz input ripple (C_{ADJ} for ADJ=25 μF)

Note 3: $\Delta V_{\text{OUT}} = 1\%$

Typical Applications




Fig. 1 Fixed Voltage Regulator





Fig. 2 1.25V Voltage Regulator



$$V_{\text{OUT}} = V_{\text{ADJ}} \left(1 + \frac{R_2}{R_1} \right) + I_{\text{ADJ}} \times R_2$$

Fig. 3 Adjustable Voltage Regulator

Electrical Characteristic Curves

Fig. 1 Minimum Load Current(Adjustable)




Fig. 2 Adjust Pin Current




Fig. 3 Temperature Stability




Fig. 4 Load Regulation




Fig. 5 Dropout Voltage





Fig. 6 Dropout Voltage - Temperature



Electrical Characteristic Curves

Fig. 7 Load Transient Response




Fig. 8 Line Transient Response





Fig. 9 Ripple Rejection



These AUK products are intended for usage in general electronic equipments (Office and communication equipment, measuring equipment, domestic electrification, etc.).

Please make sure that you consult with us before you use these AUK products in equipments which require high quality and/or reliability, and in equipments which could have major impact to the welfare of human life(atomic energy control, airplane, spaceship, traffic signal, combustion central, all types of safety device, etc.).

AUK cannot accept liability to any damage which may occur in case these AUK products were used in the mentioned equipments without prior consultation with AUK.