

# SHINDENGEN

## Schottky Rectifiers (SBD)

Single

**D5S9M**

**90V 5A**

### FEATURES

T<sub>j</sub>150

P<sub>RRSM</sub> avalanche guaranteed

Fully Isolated Molding

### APPLICATION

Switching power supply

DC/DC converter


Home Appliances, Office Equipment

Telecommunication

### OUTLINE DIMENSIONS

Case : ITO-220

Unit : mm



### RATINGS

Absolute Maximum Ratings (If not specified T ≤ 25 °C)


Item	Symbol	Conditions	Ratings	Unit
Storage Temperature	T <sub>stg</sub>		-40 ~ 150	
Operating Junction Temperature	T <sub>j</sub>		150	
Maximum Reverse Voltage	V <sub>RM</sub>		90	V
Repetitive Peak Surge Reverse Voltage	V <sub>RRSM</sub>	Pulse width 0.5ms, duty 1/40	100	V
Average Rectified Forward Current	I <sub>o</sub>	50Hz sine wave, R-load, T <sub>c</sub> =121	5	A
Peak Surge Forward Current	I <sub>FSM</sub>	50Hz sine wave, Non-repetitive 1 cycle peak value, T <sub>j</sub> =125	100	A
Repetitive Peak Surge Reverse Power	P <sub>RRSM</sub>	Pulse width 10 μs, T <sub>j</sub> =25	330	W
Dielectric Strength	V <sub>dis</sub>	Terminals to case, AC 1 minute	1.5	kV
Mounting Torque	T <sub>OR</sub>	(Recommended torque 0.3N·m)	0.5	N·m


Electrical Characteristics (If not specified T ≤ 25 °C)

Item	Symbol	Conditions	Ratings	Unit
Forward Voltage	V <sub>F</sub>	I <sub>F</sub> =5A, Pulse measurement	Max.0.75	V
Reverse Current	I <sub>R</sub>	V <sub>R</sub> =V <sub>RM</sub> , Pulse measurement	Max. 3.0	mA
Junction Capacitance	C <sub>j</sub>	f=1MHz, V <sub>R</sub> =10V	Typ.185	pF
Thermal Resistance	j <sub>C</sub>	junction to case	Max.4.5	/W

# D5S9M


## Forward Voltage











D5S9M



Reverse Current














D5S9M

Peak Surge Forward Capability



## SBD Repetitive Surge Reverse Power Derating Curve



## SBD Repetitive Surge Reverse Power Capability

