



STPS30L30CT/CG


LOW DROP POWER SCHOTTKY RECTIFIER

MAIN PRODUCT CHARACTERISTICS

I _{F(AV)}	2 x 15 A
V _{RRM}	30 V
T _j (max)	150 °C
V _F (max)	0.37 V

FEATURES AND BENEFITS

- VERY SMALL CONDUCTION LOSSES
- NEGLIGIBLE SWITCHING LOSSES
- EXTREMELY FAST SWITCHING
- LOW FORWARD VOLTAGE DROP
- LOW THERMAL RESISTANCE



DESCRIPTION

Dual center tap Schottky rectifiers suited for Switch Mode Power Supply and high frequency DC to DC converters.

Packaged in TO-220AB and D²PAK these devices are intended for use in low voltage, high frequency inverters, free-wheeling and polarity protection applications.

ABSOLUTE RATINGS (limiting values, per diode)

Symbol	Parameter			Value	Unit		
V _{RRM}	Repetitive peak reverse voltage			30	V		
I _{F(RMS)}	RMS forward current			30	A		
I _{F(AV)}	Average forward current	T _c = 140°C δ = 0.5	Per diode Per device	15 30	A		
I _{FSM}	Surge non repetitive forward current	tp = 10 ms Sinusoidal		220	A		
I _{RRM}	Peak repetitive reverse current	tp = 2 μs F = 1kHz square		1	A		
I _{RSM}	Non repetitive peak reverse current	tp = 100μs square		3	A		
T _{stg}	Storage temperature range			- 65 to + 150	°C		
T _j	Maximum operating junction temperature *			150	°C		
dV/dt	Critical rate of rise reverse voltage			10000	V/μs		

* : $\frac{dP_{tot}}{dT_j} < \frac{1}{R_{th(j-a)}}$ thermal runaway condition for a diode on its own heatsink

STPS30L30CT/CG

THERMAL RESISTANCE

Symbol	Parameter		Value	Unit
R _{th} (j-c)	Junction to case	Per diode Total	1.5 0.8	°C/W
R _{th} (c)		Coupling	0.1	°C/W

When the diodes 1 and 2 are used simultaneously :
 $\Delta T_j(\text{diode 1}) = P(\text{diode 1}) \times R_{\text{th(j-c)}}(\text{Per diode}) + P(\text{diode 2}) \times R_{\text{th(c)}}$

STATIC ELECTRICAL CHARACTERISTICS (per diode)

Symbol	Parameter	Tests Conditions		Min.	Typ.	Max.	Unit
I _R *	Reverse leakage current	T _j = 25°C	V _R = V _{RRM}			1.5	mA
		T _j = 125°C			170	350	mA
V _F *	Forward voltage drop	T _j = 25°C	I _F = 15 A			0.46	V
		T _j = 125°C	I _F = 15 A		0.33	0.37	
		T _j = 25°C	I _F = 30 A			0.57	
		T _j = 125°C	I _F = 30 A		0.43	0.5	

Pulse test : * tp = 380 μs, δ < 2%

To evaluate the conduction losses use the following equation :
 $P = 0.24x I_{F(\text{AV})} + 0.009 I_{F(\text{RMS})}^2$

Fig. 1: Average forward power dissipation versus average forward current (per diode).




Fig. 2: Average current versus ambient temperature (δ=0.5) (per diode).




Fig. 3: Non repetitive surge peak forward current versus overload duration (maximum values) (per diode).




Fig. 5: Reverse leakage current versus reverse voltage applied (typical values) (per diode).




Fig. 7: Forward voltage drop versus forward current (maximum values - per diode).




Fig. 4: Relative variation of thermal transient impedance junction to case versus pulse duration.




Fig. 6: Junction capacitance versus reverse voltage applied (typical values) (per diode).






Fig. 8: Thermal resistance junction to ambient versus copper surface under tab (epoxy printed circuit board FR4, $e(\text{Cu}) = 35\ \mu\text{m}$) (STPS30L30CG).




STPS30L30CT/CG

PACKAGE MECHANICAL DATA TO-220AB




REF.	DIMENSIONS			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	4.40	4.60	0.173	0.181
C	1.23	1.32	0.048	0.051
D	2.40	2.72	0.094	0.107
E	0.49	0.70	0.019	0.027
F	0.61	0.88	0.024	0.034
F1	1.14	1.70	0.044	0.066
F2	1.14	1.70	0.044	0.066
G	4.95	5.15	0.194	0.202
G1	2.40	2.70	0.094	0.106
H2	10	10.40	0.393	0.409
L2	16.4 typ.		0.645 typ.	
L4	13	14	0.511	0.551
L5	2.65	2.95	0.104	0.116
L6	15.25	15.75	0.600	0.620
L7	6.20	6.60	0.244	0.259
L9	3.50	3.93	0.137	0.154
M	2.6 typ.		0.102 typ.	
Diam.	3.75	3.85	0.147	0.151

- Cooling method: C
- Recommended torque value: 0.55 m.N
- Maximum torque value: 0.70 m.N

PACKAGE MECHANICAL DATA
D²PAK


REF.	DIMENSIONS			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	4.40	4.60	0.173	0.181
A1	2.49	2.69	0.098	0.106
A2	0.03	0.23	0.001	0.009
B	0.70	0.93	0.027	0.037
B2	1.14	1.70	0.045	0.067
C	0.45	0.60	0.017	0.024
C2	1.23	1.36	0.048	0.054
D	8.95	9.35	0.352	0.368
E	10.00	10.40	0.393	0.409
G	4.88	5.28	0.192	0.208
L	15.00	15.85	0.590	0.624
L2	1.27	1.40	0.050	0.055
L3	1.40	1.75	0.055	0.069
M	2.40	3.20	0.094	0.126
R	0.40 typ.		0.016 typ.	
V2	0°	8°	0°	8°

FOOT PRINT (in millimeters)

Ordering type	Marking	Package	Weight	Base qty	Delivery mode
STPS30L30CT	STPS30L30CT	TO-220AB	2g	50	Tube
STPS30L30CG	STPS30L30CG	D ² PAK	1.8g	50	Tube
STPS30L30CG-TR	STPS30L30CG	D ² PAK	1.8g	1000	Tape & reel

- Epoxy meets UL94,V0

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics

© 1999 STMicroelectronics - Printed in Italy - All rights reserved.

STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - China - Finland - France - Germany - Hong Kong - India - Italy - Japan - Malaysia
Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - U.S.A.

<http://www.st.com>