

POWER SCHOTTKY RECTIFIERS

MAIN PRODUCTS CHARACTERISTICS

$I_{F(av)}$	2 x 20 A
V_{RRM}	45 V
$T_j (max)$	175 °C
$V_F (max)$	0.63 V


FEATURES AND BENEFITS

- VERY SMALL CONDUCTION LOSSES
- NEGLIGIBLE SWITCHING LOSSES
- EXTREMELY FAST SWITCHING
- LOW THERMAL RESISTANCE

DESCRIPTION

Dual center tap Schottky rectifier suited for switchmode power supply and high frequency DC to DC converters.

Packaged either in SOT-93 or TO-247 this device is intended for use in low voltage, high frequency inverters, free wheeling and polarity protection applications.



ABSOLUTE RATINGS (limiting values, per diode)

Symbol	Parameter			Value	Unit
V _{RRM}	Repetitive peak reverse voltage			45	V
I _{F(RMS)}	RMS forward current			30	A
I _{F(AV)}	Average forward current	T _c = 150°C δ = 0.5	Per diode Per device	20 40	A
I _{FSM}	Surge non repetitive forward current	tp = 10 ms sinusoidal		220	A
I _{RRM}	Repetitive Peak reverse current	tp = 2 μs square F = 1kHz		1	A
I _{RSM}	Non repetitive peak reverse current	tp = 100 μs square		3	A
T _{stg}	Storage temperature range			- 65 to + 175	°C
T _j	Maximum operating junction temperature *			175	°C
dV/dt	Critical rate of rise of reverse voltage			10000	V/μs

* : $\frac{dP_{tot}}{dT_j} < \frac{1}{R_{th(j-a)}}$ thermal runaway condition for a diode on its own heatsink

THERMAL RESISTANCES

Symbol	Parameter		Value	Unit
$R_{th(j-c)}$	Junction to case	Per diode total	1.5 0.8	$^{\circ}\text{C/W}$
$R_{th(c)}$		Coupling	0.1	

When the diodes 1 and 2 are used simultaneously :

$$\Delta T_J(\text{diode 1}) = P(\text{diode 1}) \times R_{th(j-c)} (\text{Per diode}) + P(\text{diode 2}) \times R_{th(c)}$$

STATIC ELECTRICAL CHARACTERISTICS (per diode)

Symbol	Parameter	Tests Conditions		Min.	Typ.	Max.	Unit
I_R^*	Reverse leakage current	$T_j = 25^{\circ}\text{C}$	$V_R = V_{RRM}$			200	μA
		$T_j = 125^{\circ}\text{C}$			11	40	mA
V_F^*	Forward voltage drop	$T_j = 125^{\circ}\text{C}$	$I_F = 20\text{ A}$		0.56	0.63	V
		$T_j = 25^{\circ}\text{C}$	$I_F = 40\text{ A}$			0.94	
		$T_j = 125^{\circ}\text{C}$	$I_F = 40\text{ A}$		0.7	0.83	

Pulse test : $* t_p = 380\text{ }\mu\text{s}$, $\delta < 2\%$

To evaluate the conduction losses use the following equation :

$$P = 0.46 \times I_{F(AV)} + 0.0085 I_F^2 (RMS)$$

Fig. 1: Average forward power dissipation versus average forward current (per diode).




Fig. 2: Average current versus ambient temperature (per diode).




Fig. 3: Non repetitive surge peak forward current versus overload duration (maximum values) (per diode).




Fig. 4: Relative variation of thermal transient impedance junction to case versus pulse duration.




Fig. 5: Reverse leakage current versus reverse voltage applied (typical values) (per diode).




Fig. 6: Junction capacitance versus reverse voltage applied (typical values) (per diode).







Fig. 7: Forward voltage drop versus forward current (maximum values) (per diode).



PACKAGE MECHANICAL DATA
SOT-93



PACKAGE MECHANICAL DATA
TO-247


Type	Marking	Package	Weight	Base qty	Delivery mode
STPS4045CP	STPS4045CP	SOT-93	3.97 g.	30	Tube
STPS4045CW	STPS4045CW	TO-247	4.46 g.	30	Tube

- Cooling method: by conduction (C)
- Recommended torque value: 0.8 N.m
- Maximum torque value: 1.0 N.m.
- Epoxy meets UL94,V0

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied.

STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics

© 1999 STMicroelectronics - Printed in Italy - All rights reserved.

STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - China - Finland - France - Germany - Hong Kong - India - Italy - Japan - Malaysia
 Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - U.S.A.

<http://www.st.com>