

W005 – W10

1.5A WOM 桥式整流器

1.5A WOM BRIDGE RECTIFIERS

最大额定值、电性 MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.

型号 TYPE	最大反向 峰值电压 Maximum Peak Reverse Voltage	最大平均 正向电流 Maximum Average Forward Output Current @T _A =40°C	最大正向 浪涌电流 Maximum Forward Peak Surge Current @ 8.3ms Superimposed	最大正向 峰值电压 Maximum DC Forward Voltage drop per element at I _F =1.0ADC	最大反向 电 流 Maximum DC Reverse Current at rated DC Blocking Voltage per element		结 温 Operating Junction Temperature	外型尺寸 Package Dimensions
	PRV V _{PK}	I _O A _{AV}	I _{FM} (Surge) A _{PK}	V _F V _{PK}	I _R 25°C T _A μADC	125°C T _A μADC	T _J °C	
W005 W01 W02 W04 W06 W08 W10	50 100 200 400 600 800 1000	1.5	50	1.1	10	500	125	WOMRC-2

