

FEATURES :

- HIGH POWER
P_{1dB} = 37.5 dBm at 13.75 GHz to 14.5 GHz
- BROAD BAND INTERNALLY MATCHED
- HIGH GAIN
G_{1dB} = 5.5 dB at 13.75 GHz to 14.5 GHz
- HERMETICALLY SEALED PACKAGE

RF PERFORMANCE SPECIFICATIONS (Ta = 25°C)

CHARACTERISTICS	SYMBOL	CONDITION	UNIT	MIN.	TYP.	MAX.
Output Power at 1dB Compression Point	P _{1dB}	V _{DS} = 9 V f = 13.75 ~ 14.5 GHz	dBm	37.0	37.5	—
Power Gain at 1dB Compression Point	G _{1dB}		dB	4.5	5.5	—
Drain Current	I _{DS}		A	—	2.0	2.5
Power Added Efficiency	η _{add}		%	—	22	—
Channel-Temperature Rise	ΔT _{Ch}	V _{DS} × I _{DS} × R _{th(c-c)}	°C	—	—	80

ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTICS	SYMBOL	CONDITION	UNIT	MIN.	TYP.	MAX.
Transconductance	gm	V _{DS} = 3 V I _{DS} = 2.4 A	mS	—	1400	—
Pinch-off Voltage	V _{GSoff}	V _{DS} = 3 V I _{DS} = 72 mA	V	-2.0	-3.5	-5.0
Saturated Drain Current	I _{DSS}	V _{DS} = 3 V V _{GS} = 0 V	A	—	5.0	5.7
Gate-Source Breakdown Voltage	V _{GSO}	I _{GS} = -72 μA	V	-5	—	—
Thermal Resistance	R _{th(c-c)}	Channel to Case	°C/W	—	3.0	3.7


- ★ The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA for any infringements of patents or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of TOSHIBA or others.
- ★ The information contained herein may be changed without prior notice. It is therefore advisable to contact TOSHIBA before proceeding with the design of equipment incorporating this product.



ABSOLUTE MAXIMUM RATINGS (Ta = 25°C)

CHARACTERISTICS	SYMBOL	UNIT	RATING
Drain-Source Voltage	V _{DS}	V	15
Gate-Source Voltage	V _{GS}	V	-5
Drain Current	I _{DS}	A	5.7
Total Power Dissipation (T _C = 25°C)	P _T	W	30
Channel Temperature	T _{ch}	°C	175
Storage Temperature	T _{stg}	°C	-65~175

PACKAGE OUTLINE (2-9D1B)




HANDLING PRECAUTIONS FOR PACKAGED TYPE


Soldering iron should be grounded and the operating time should not exceed 10 seconds at 260°C.

RF PERFORMANCES


Output Power vs. Frequency



Output Power vs. Input Power



POWER DISSIPATION VS. CASE TEMPERATURE



Copyright Each Manufacturing Company.

All Datasheets cannot be modified without permission.

This datasheet has been download from :

www.AllDataSheet.com

100% Free DataSheet Search Site.

Free Download.

No Register.

Fast Search System.

www.AllDataSheet.com