


SILICON ABRUPT JUNCTION TUNING VARACTOR

DESCRIPTION:

The **AT9017-10** is an Epitaxial Silicon Abrupt Junction Microwave Tuning Varactor. This Device is Passivated With Silicon Dioxide Which Results in Very Low Leakage Current. The Capacitance Voltage Relationship Closley Approximates Square Law (n = 0.5).

MAXIMUM RATINGS

Ic	100 mA				
V _{CE}	90 V				
P _{DISS}	250 mW @ T _C = 25 °C				
TJ	-65 °C to +150 °C				
T _{STG}	-65 °C to +150 °C				



CHARACTERISTICS T_C = 25 °C

SYMBOL	TEST CONDITIONS		MINIMUM	TYPICAL	MAXIMUM	UNITS
V_{B}	$I_R = 10 \mu A$		90			V
C _T	$V_R = 4.0 \text{ V}$	f = 1.0 MHz	19.80	22.00	24.20	pF
ΔC_{T}	$C_{T} = 0 \text{ V} / C_{T} = 8.0 \text{ V}$	f = 1.0 MHz	9.4			RATIO
Q	V _R = 4.0 V	f = 50 MHz	600			
T _C	V _R = 4.0 V				300	Ppm/ ^o C