

# NPN SILICON RF POWER TRANSISTOR

**DESCRIPTION:**


The **ASI MLN2030SS** is Designed for Class A linear Applications up to 2.0 GHz.

**FEATURES:**

- Class A Operation
- $P_G = 10$  dB at 1.0 W/2.0 GHz
- **Omnigold™** Metalization System

**MAXIMUM RATINGS**

$I_C$	10 A
$V_{CB}$	60 V
$V_{CE}$	35 V
$P_{DISS}$	140 W @ $T_C = 25$ °C
$T_J$	-65 °C to +200 °C
$T_{STG}$	-65 °C to +150 °C
$\theta_{JC}$	20 °C/W

**PACKAGE STYLE .205 4L STUD**


DIM	MINIMUM inches / mm	MAXIMUM inches / mm
A	.976 / 24.800	1.000 / 25.4000
B	.976 / 24.800	1.000 / 25.4000
C	.028 / 0.700	.031 / 0.800
D	.138 / 3.500	
E	.161 / 4.100	.196 / 5.000
F	.098 / 2.500	.110 / 2.800
G	.200 / 5.100	.208 / 5.300
H	.004 / 0.100	.006 / 0.150
I	.425 / 10.800	.465 / 11.800
J	.200 / 5.100	2.05 / 5.200

**ORDER CODE: ASI10633**
**CHARACTERISTICS**  $T_C = 25$  °C

SYMBOL	TEST CONDITIONS	MINIMUM	TYPICAL	MAXIMUM	UNITS
$BV_{CEO}$	$I_C = 50$ mA	35			V
$BV_{CER}$	$I_C = 50$ mA $R_{BE} = 10$ $\Omega$	60			V
$BV_{EBO}$	$I_E = 10$ mA	4.0			V
$I_{CES}$	$V_E = 28$ V			5.0	mA
$h_{FE}$	$V_{CE} = 5.0$ V $I_C = 1.0$ A	10		100	---
$C_{ob}$	$V_{CB} = 28$ V $f = 1.0$ MHz			5.0	pF
$P_{GE}$	$V_{CE} = 18$ V $I_{CQ} = 220$ mA $f = 2.0$ GHz $P_{OUT} = 1.0$ W	10			dB