

Toshiba CMOS Digital Integrated Circuit Silicon Monolithic

# TC7MB3245FK

## Octal Bus Switch


The TC7MB3245FK provides eight bits of high-speed TTL-compatible bus switching in a standard '245 device pinout. The low on-state resistance of the switch allows connections to be made with minimal propagation delay.

The device is organized as one 8-bit switch. When output enable ( $\overline{OE}$ ) is low, the switch is on and port A is connected to port B. When  $\overline{OE}$  is high, the switch is open and a high-impedance state exists between the two ports.

All inputs are equipped with protection circuits against static discharge.


### Features

- Operating voltage:  $V_{CC} = 4.5\sim 5.5\text{ V}$
- High speed:  $t_{pd} = 0.25\text{ ns (max)}$
- Low on resistance:  $R_{ON} = 5\ \Omega\text{ (typ.)}$
- ESD performance: Human body model  $> \pm 2000\text{ V}$   
Machine model  $> \pm 200\text{ V}$
- Compatible with TTL outputs (control inputs)
- Package: VSSOP (US20)
- Pin compatible with the 74xx245 type.  
Functionally equivalent to (FST/CBT) 3245.



Weight: 0.03 g (typ.)

### Pin Assignment (top view)



NC-No Internal Connection

000630EBA1

• TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such TOSHIBA products could cause loss of human life, bodily injury or damage to property.

In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the "Handling Guide for Semiconductor Devices," or "TOSHIBA Semiconductor Reliability Handbook" etc..

• The Toshiba products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These Toshiba products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of Toshiba products listed in this document shall be made at the customer's own risk.

• The products described in this document are subject to the foreign exchange and foreign trade laws.


• The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.

• The information contained herein is subject to change without notice.

## Truth Table

Inputs	Function
$\overline{OE}$	
L	A port = B port
H	Disconnect

## System Diagram



## Maximum Ratings

Characteristics	Symbol	Rating	Unit
Power supply range	$V_{CC}$	-0.5~7.0	V
DC input voltage	$V_{IN}$	-0.5~7.0	V
DC switch voltage	$V_S$	-0.5~7.0	V
Input diode current	$I_{IK}$	-50	mA
Continuous channel circuit	$I_S$	128	mA
Power dissipation	$P_D$	180	mW
DC $V_{CC}$ /ground current	$I_{CC}/I_{GND}$	$\pm 100$	mA
Storage temperature	$T_{stg}$	-65~150	$^{\circ}C$

## Recommended Operating Conditions

Characteristics	Symbol	Rating	Unit
Supply voltage	$V_{CC}$	4.5~5.5	V
Input voltage	$V_{IN}$	0~5.5	V
Switch voltage	$V_S$	0~5.5	V
Operating temperature	$T_{opr}$	-40~85	$^{\circ}C$
Input rise and fall time	dt/dv	0~10	ns/V

## Electrical Characteristics

### DC Characteristics (Ta = -40~85°C)

Characteristics		Symbol	Test Condition		Min	Typ. (Note1)	Max	Unit
Input voltage	"H" level	V <sub>IH</sub>	—		2.0	—	—	V
	"L" level	V <sub>IL</sub>	—		—	—	0.8	
Input leakage current		I <sub>IN</sub>	V <sub>IN</sub> = 0~5.5 V		5.5	—	±1.0	μA
Off-STATE leakage current (switch off)		I <sub>SZ</sub>	A, B = 0~5.5 V, $\overline{OE} = V_{CC}$		0~5.5	—	±1.0	μA
ON resistance  (Note2)	R <sub>ON</sub>	V <sub>IS</sub> = 0 V	I <sub>IS</sub> = 64 mA		4.5	—	5	Ω
			I <sub>IS</sub> = 30 mA		4.5	—	5	
		V <sub>IS</sub> = 2.4 V, I <sub>IS</sub> = 15 mA		4.5	—	10	15	
Quiescent supply current		I <sub>CC</sub>	V <sub>IN</sub> = V <sub>CC</sub> or GND, I <sub>OUT</sub> = 0		5.5	—	10	μA
Increase in I <sub>CC</sub> per input		ΔI <sub>CC</sub>	V <sub>IN</sub> = 3.4 V (one input)		5.5	—	2.5	mA

Note1: Typical values are at V<sub>CC</sub> = 5 V, Ta = 25°C.

Note2: Measured by the voltage drop between A and B pins at the indicated current through the switch. On resistance is determined by the lower of the voltages on the two (A or B) pins.

### AC Characteristics (Ta = -40~85°C)

Characteristics		Symbol	Test Condition		Min	Max	Unit
Propagation delay time (bus to bus)	t <sub>pLH</sub>	Figure 1, Figure 2	(Note3)	4.5	—	0.25	ns
	t <sub>pHL</sub>						
Output enable time	t <sub>pZL</sub>	Figure 1, Figure 3		4.5	—	5.9	ns
	t <sub>pZH</sub>						
Output disable time	t <sub>pLZ</sub>	Figure 1, Figure 3		4.5	—	5.9	ns
	t <sub>pHZ</sub>						


Note3: This parameter is guaranteed by design but is not tested. The bus switch contributes no propagation delay other than the RC delay of the typical On resistance of the switch and the 50 pF load capacitance, when driven by an ideal voltage the source (zero output impedance).

### Capacitive Characteristics (Ta = 25°C)

Characteristics		Symbol	Test Condition		Typ.	Unit	
							V <sub>CC</sub> (V)
Control pin input capacitance		C <sub>IN</sub>	(Note4)		5.0	3	pF
Switch terminal capacitance		C <sub>I/O</sub>	$\overline{OE} = V_{CC}$		5.0	10	pF


Note4: Parameter guaranteed by design.

**AC Test Circuit**




**Figure 1**

**AC Waveform**



**Figure 2  $t_{pLH}$ ,  $t_{pHL}$**





**Figure 3  $t_{pLZ}$ ,  $t_{pHZ}$ ,  $t_{pZL}$ ,  $t_{pZH}$**

Package Dimensions

VSSOP20-P-0030-0.50

Unit : mm



Weight: 0.03 g (typ.)