


APT PART NUMBER	DRAIN-SOURCE VOLTAGE BVDSS (VOLTS)	ON RESISTANCE RDS(ON) (OHMS)	DRAIN CURRENT		INPUT CAPACITANCE CISS (pF)	POWER DISSIPATION PD(MAX) (WATTS)	NOTES	CASE STYLE AND DEVICE TYPE
			ID (CONT) (AMPS)	IDM (PULSED) (AMPS)				
APT1001RAN	1000	1.00	9.5	38.0	2450	230	1	TO-3 (TO-204AA)
APT1001R2AN	1000	1.20	9.0	36.0	2450	230	1	
APT1002RAN	1000	2.00	6.0	24.0	1750	198	1	
APT1002R4AN	1000	2.40	5.5	22.0	1750	198	1	
APT1003R5AN	1000	3.50	4.0	16.0	880	150	1	
APT1004R2AN	1000	4.20	3.5	14.0	880	150	1	
APT901RAN	900	1.00	9.5	38.0	2450	230	1	
APT901R2AN	900	1.20	9.0	36.0	2450	230	1	
APT902RAN	900	2.00	6.0	24.0	1750	198	1	
APT902R4AN	900	2.40	5.5	22.0	1750	198	1	
APT903R5AN	900	3.50	4.0	16.0	880	150	1	
APT904R2AN	900	4.20	3.5	14.0	880	150	1	
APT8075AN	800	0.75	11.0	44.0	2450	230	1	
APT8090AN	800	0.90	10.0	40.0	2450	230	1	
APT801R2AN	800	1.20	8.0	32.0	1750	198	1	
APT801R4AN	800	1.40	7.5	30.0	1750	198	1	
APT802RAN	800	2.00	5.5	22.0	880	150	1	
APT802R4AN	800	2.40	5.0	20.0	880	150	1	
APT7575AN	750	0.75	11.0	44.0	2450	230	1	
APT7590AN	750	0.90	10.0	40.0	2450	230	1	
APT751R2AN	750	1.20	8.0	32.0	1750	198	1	
APT751R4AN	750	1.40	7.5	30.0	1750	198	1	
APT752RAN	750	2.00	5.5	22.0	880	150	1	
APT752R4AN	750	2.40	5.0	20.0	880	150	1	
APT6040AN	600	0.40	15.5	62.0	2400	230	1	
APT6045AN	600	0.45	14.5	58.0	2400	230	1	
APT6060AN	600	0.60	11.5	46.0	1700	198	1	
APT6070AN	600	0.70	10.5	42.0	1700	198	1	
APT601R2AN	600	1.20	7.0	28.0	850	150	1	
APT601R6AN	600	1.60	6.0	24.0	850	150	1	
APT5540AN	550	0.40	15.5	62.0	2400	230	1	
APT5545AN	550	0.45	14.5	58.0	2400	230	1	
APT5560AN	550	0.60	11.5	46.0	1700	198	1	
APT5570AN	550	0.70	10.5	42.0	1700	198	1	
APT551R2AN	550	1.20	7.0	28.0	850	150	1	
APT551R6AN	550	1.60	6.0	24.0	850	150	1	
APT5025AN	500	0.25	20.0	80.0	2400	230	1	
APT5030AN	500	0.30	18.0	72.0	2400	230	1	
APT5040AN	500	0.40	14.5	58.0	1700	198	1	
APT5050AN	500	0.50	13.0	52.0	1700	198	1	
APT5085AN	500	0.85	8.5	34.0	850	150	1	
APT501R1AN	500	1.10	7.5	30.0	850	150	1	
APT4525AN	450	0.25	20.0	80.0	2400	230	1	
APT4530AN	450	0.30	18.0	72.0	2400	230	1	
APT4540AN	450	0.40	14.5	58.0	1700	198	1	
APT4550AN	450	0.50	13.0	52.0	1700	198	1	
APT4585AN	450	0.85	8.5	34.0	850	150	1	
APT451R1AN	450	1.10	7.5	30.0	850	150	1	
APT4020AN	400	0.20	22.5	90.0	2400	230	1	
APT4025AN	400	0.25	20.0	80.0	2400	230	1	
APT4030AN	400	0.30	17.0	68.0	1700	198	1	
APT4040AN	400	0.40	14.5	58.0	1700	198	1	
APT4055AN	400	0.55	10.5	42.0	850	150	1	
APT4080AN	400	0.80	8.5	34.0	850	150	1	
APT3520AN	350	0.20	22.5	90.0	2400	230	1	
APT3525AN	350	0.25	20.0	80.0	2400	230	1	
APT3530AN	350	0.30	17.0	68.0	1700	198	1	
APT3540AN	350	0.40	14.5	58.0	1700	198	1	
APT3555AN	350	0.55	10.5	42.0	850	150	1	
APT3580AN	350	0.80	8.5	34.0	850	150	1	



HERMETIC COMMERCIAL AND HI-REL MILITARY N-CHANNEL MOSFET



NOTE 1. - CURRENTLY AVAILABLE