

<b>SANYO</b>	No.3235	<b>2SC4482</b>
	NPN Epitaxial Planar Silicon Transistor	
High-Current Switching Applications		

**Features**

- Low saturation voltage
- Large current capacity
- Fast switching speed

**Absolute Maximum Ratings at Ta = 25°C**

			unit
Collector to Base Voltage	V <sub>CB0</sub>	60	V
Collector to Emitter Voltage	V <sub>CEO</sub>	20	V
Emitter to Base Voltage	V <sub>EBO</sub>	6	V
Collector Current	I <sub>C</sub>	5	A
Collector Current(Pulse)	I <sub>CP</sub>	8	A
Collector Dissipation	P <sub>C</sub>	1	W
Junction Temperature	T <sub>j</sub>	150	°C
Storage Temperature	T <sub>stg</sub>	-55 to +150	°C


**Electrical Characteristics at Ta = 25°C**

			min	typ	max	unit
Collector Cutoff Current	I <sub>CB0</sub>	V <sub>CB</sub> = 50V, I <sub>E</sub> = 0			100	nA
Emitter Cutoff Current	I <sub>EBO</sub>	V <sub>EB</sub> = 5V, I <sub>C</sub> = 0			100	nA
DC Current Gain	h <sub>FE</sub> (1)	V <sub>CE</sub> = 2V, I <sub>C</sub> = 500mA	140*		560*	
	h <sub>FE</sub> (2)	V <sub>CE</sub> = 2V, I <sub>C</sub> = 3A	95			
Gain-Bandwidth Product	f <sub>T</sub>	V <sub>CE</sub> = 10V, I <sub>C</sub> = 50mA		150		MHz
Output Capacitance	c <sub>ob</sub>	V <sub>CB</sub> = 10V, f = 1MHz		45		pF
C-E Saturation Voltage	V <sub>CE(sat)</sub>	I <sub>C</sub> = 3A, I <sub>B</sub> = 60mA		220	500	mV
B-E Saturation Voltage	V <sub>BE(sat)</sub>	I <sub>C</sub> = 3A, I <sub>B</sub> = 60mA			1.5	V
C-B Breakdown Voltage	V <sub>(BR)CBO</sub>	I <sub>C</sub> = 10μA, I <sub>E</sub> = 0	60			V
C-E Breakdown Voltage	V <sub>(BR)CEO</sub>	I <sub>C</sub> = 1mA, R <sub>BE</sub> = ∞	20			V
E-B Breakdown Voltage	V <sub>(BR)EBO</sub>	I <sub>E</sub> = 10μA, I <sub>C</sub> = 0	6			V
Turn-on Time	t <sub>on</sub>	See specified Test Circuit.		30		ns
Storage Time	t <sub>stg</sub>	∞		300		ns
Fall Time	t <sub>f</sub>	∞		40		ns

\* : The 2SC4482 is classified by 500mA h<sub>FE</sub> as follows :


140	S	280	200	T	400	280	U	560
-----	---	-----	-----	---	-----	-----	---	-----









**Switching Time Test Circuit**





**Package Dimensions 2064**

(unit: mm)







- No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.
- Anyone purchasing any products described or contained herein for an above-mentioned use shall:
  - ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use:
  - ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.