

# 2SB1169, 2SB1169A

## Silicon PNP Epitaxial Planar Type

### Power Amplifier


#### ■ Features

- High DC current gain ( $h_{FE}$ ) and good linearity
- Low collector-emitter voltage ( $V_{CE}$ )
- "I Type" package configuration with a cooling fin for direct soldering on PC board of a small-size electronic equipment

#### ■ Absolute Maximum Ratings ( $T_c=25^\circ\text{C}$ )

Item	Symbol	Value	Unit
Collector-base voltage	2SB1169	-60	V
	2SB1169A	-80	
Collector-emitter voltage	2SB1169	-60	V
	2SB1169A	-80	
Emitter-base voltage	$V_{EBO}$	-5	V
Peak collector current	$I_{CP}$	-2	A
Collector current	$I_C$	-1	A
Collector power dissipation	$T_c=25^\circ\text{C}$	15	W
	$T_a=25^\circ\text{C}$	1.3	
Junction temperature	$T_j$	150	$^\circ\text{C}$
Storage temperature	$T_{stg}$	-55 ~ +150	$^\circ\text{C}$

#### ■ Package Dimensions



\*Surface-mount type is also available.  
(Refer to p.81.)

#### ■ Electrical Characteristics ( $T_c=25^\circ\text{C}$ )

Item	Symbol	Condition	min.	typ.	max.	Unit
Collector cutoff current	$I_{CEO}$	$V_{CB} = -30\text{ V}, I_E = 0$			-300	$\mu\text{A}$
		$V_{CB} = -60\text{ V}, I_E = 0$			-300	
Collector cutoff current	$I_{CES}$	$V_{CE} = -60\text{ V}, V_{BE} = 0$			-200	$\mu\text{A}$
		$V_{CE} = -80\text{ V}, V_{BE} = 0$			-200	
Emitter cutoff current	$I_{EBO}$	$V_{EB} = -5\text{ V}, I_C = 0$			-1	mA
Collector-emitter voltage	$V_{CEO}$	$I_C = -30\text{ mA}, I_B = 0$	-60			V
			-80			
DC current gain	$h_{FE1}^*$	$V_{CE} = -4\text{ V}, I_C = -0.2\text{ A}$	40		450	
		$V_{CE} = -4\text{ V}, I_C = -1\text{ A}$	15			
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C = -1\text{ A}, I_R = -0.125\text{ A}$			-1	V
Base-emitter saturation voltage	$V_{BE}$	$V_{CE} = -4\text{ V}, I_C = -1\text{ A}$			-1.3	V
Transition frequency	$f_T$	$V_{CE} = -10\text{ V}, I_C = -0.1\text{ A}, f = 10\text{ MHz}$		40		MHz
Turn-on time	$t_{on}$	$I_C = -1\text{ A}, I_{B1} = -0.1\text{ A}, I_{B2} = 0.1\text{ A}, V_{CC} = -50\text{ V}$		0.5		$\mu\text{s}$
Storage time	$t_{stg}$			1.2		$\mu\text{s}$
Collector current fall time	$t_f$			0.3		$\mu\text{s}$

#### \* $h_{FE1}$ Classifications

Class	R	Q	P	O
$h_{FE1}$	40~90	70~150	120~250	200~450

