

One chip driver for slim CD-ROM/RW, DVD-ROM

BH6546KV


● Description

BH6546KV is a 4-channel PWM driver that drives spindle/slide motor, and focus/track actuator coil of optical disc. In high speed and 180° PWM driving slim disc, the spindle driver can achieve low vibration/low noise.

● Features

- 1) Low vibration/low noise by 180° PWM driving
- 2) Charge-pump circuit is not necessary for output due to complement power MOSFET.
- 3) Low power consumption due to low ON resistance
 Spindle driver output: 0.5Ω (Typ.)
 Slide/Focus/Tracking driver output: 1.2Ω (Typ.)
- 4) 1 phase/3 phase FG output can be switched by FG switching pin.
- 5) VQFP48C contributes to make the set smaller and thinner.

● Dimension (Units : mm)



VQFP48C

● Applications

CD-ROM, CD-RW, DVD-ROM

● Absolute Maximum Ratings (Ta=25°C)

Parameter	Symbol	Limits	Unit
Power MOS supply voltage	PVcc	6	V
Control circuit supply voltage	Vcc	6	V
Maximum output current	IoMAX	3 *1	A
Power dissipation	Pd	1.18□*2	W
Operating temperature range	Topr	-30 ~ +85	°C
Storage temperature range	Tstg	-55 ~ +150	°C

*1 Intermittent current at maximum applied time of 5msec, 1/10 duty (Max.)

*2 Derating : 9.5mW/°C for operation above Ta=25°C

On less than 3% (percentage occupied by copper foil), 70mmx70mm, t=1.6mm, glass epoxy mounting.


● Recommended Operating Conditions

Parameter	Symbol	Limits	Unit
Power MOS supply voltage	PVcc	3.0 ~ 5.5	V
Control circuit supply voltage	Vcc	4.0 ~ 5.5	V
Ambient temperature	Ta	-10 ~ +70	°C

- Electrical characteristics (Unless otherwise noted; $T_a=25^\circ\text{C}$, $V_{cc}=5\text{V}$, $PV_{cc}=5\text{V}$, $V_{ref}=1.65\text{V}$, $R_{L(act,SL)}=8\Omega+47\mu\text{H}$, $R_{L(SP)}=2\Omega+47\mu\text{H}$, $R_{NF}=0.33\Omega$)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Current at stand-by mode	IST	—	—	0.1	mA	
Current at no signal	ICC	—	5	10	mA	
PWM driver			□	□		
Input dead zone (One side) (CH1,2)	VDZ1,2	0	10	30	mV	
Input dead zone (One side) (CH3)	VDZ3	0	20	50	mV	
Output offset voltage	VOO	-50	—	50	mV	
Voltage gain	GVC	12	14	16	dB	
Oscillation frequency	f3CH	240	300	360	kHz	
Output ON resistance (Top+Bottom)	RON	—	1.2	2.1	Ω	$I_o=500\text{mA}$
Three phase motor driver			□	□		
Hall input level	VHI	200	—	—	mVpp	
Input dead zone (One side)	VDZSP	2	30	100	mV	
I/O gain	gm	0.35	0.50	0.65	Arms/V	$SPRNF=0.33\Omega$
Oscillation frequency	fSP	65	85	105	kHz	
Output ON resistance (Top+Bottom)	RONSP	—	0.5	1.0	Ω	$I_o=500\text{mA}$
Output limit voltage	VLIMSP	0.16	0.20	0.24	V	$RNF=0.33\Omega$
Others						
Vref descent mute	VMVref	—	0.7	1.0	V	
Vcc descent mute	VMVcc	3.2	3.6	4.0	V	

- Application Circuit



Notes

- No technical content pages of this document may be reproduced in any form or transmitted by any means without prior permission of ROHM CO.,LTD.
- The contents described herein are subject to change without notice. The specifications for the product described in this document are for reference only. Upon actual use, therefore, please request that specifications to be separately delivered.
- Application circuit diagrams and circuit constants contained herein are shown as examples of standard use and operation. Please pay careful attention to the peripheral conditions when designing circuits and deciding upon circuit constants in the set.
- Any data, including, but not limited to application circuit diagrams information, described herein are intended only as illustrations of such devices and not as the specifications for such devices. ROHM CO.,LTD. disclaims any warranty that any use of such devices shall be free from infringement of any third party's intellectual property rights or other proprietary rights, and further, assumes no liability of whatsoever nature in the event of any such infringement, or arising from or connected with or related to the use of such devices.
- Upon the sale of any such devices, other than for buyer's right to use such devices itself, resell or otherwise dispose of the same, no express or implied right or license to practice or commercially exploit any intellectual property rights or other proprietary rights owned or controlled by
- ROHM CO., LTD. is granted to any such buyer.
- Products listed in this document use silicon as a basic material.
Products listed in this document are no antiradiation design.

The products listed in this document are designed to be used with ordinary electronic equipment or devices (such as audio visual equipment, office-automation equipment, communications devices, electrical appliances and electronic toys).

Should you intend to use these products with equipment or devices which require an extremely high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), please be sure to consult with our sales representative in advance.

About Export Control Order in Japan

Products described herein are the objects of controlled goods in Annex 1 (Item 16) of Export Trade Control Order in Japan.

In case of export from Japan, please confirm if it applies to "objective" criteria or an "informed" (by MITI clause) on the basis of "catch all controls for Non-Proliferation of Weapons of Mass Destruction.