

High efficiency, single-digit numeric displays


LA-6000 Series

The LA-6000 series are LED numeric displays designed to be used in bright locations. Red, orange, yellow and green are available, and they are suitable for use in a wide range of applications.

●Features

- 1) Height of character : 14.22 mm.
- 2) Common anode and common cathode configurations are available for each color.
- 3) Each segment has independent pin connections making static drive possible.
- 4) High efficiency reflectors are used to achieve a bright, clear display.
- 5) The package surface is painted gray and the segments are milky white.


●External dimensions (Units: mm)



●Selection guide


Emitting color	Red	Orange	Yellow	Green
	Common			
Anode	LA-6760	LA-6660	LA-6860	LA-6460
Cathode	LA-6780	LA-6680	LA-6880	LA-6480

●Pin assignments



Pin No.	Function
1	Segment "e"
2	Segment "d"
3	Common
4	Segment "c"
5	D.P.
6	Segment "b"
7	Segment "a"
8	Common
9	Segment "f"
10	Segment "g"

● Internal circuit schematic (example of common anode)



● Absolute maximum ratings ($T_a = 25^\circ\text{C}$)

Parameter	Symbol	Red	Orange	Yellow	Green	Unit
		LB-6710 / 6740	LB-6610 / 6640	LB-6810 / 6840	LB-6410 / 6440	
Power dissipation	P_D	960	960	960	960	mW
Power dissipation	P_D / seg	60	60	60	60	mW
Forward current	I_F	20	20	20	20	mA
Peak forward current	I_{FP}	60*	60*	60*	60*	mA
Reverse voltage	V_R	5	5	5	5	V
Operating temperature	T_{opr}	-25~+85				$^\circ\text{C}$
Storage temperature	T_{stg}	-30~+100				$^\circ\text{C}$

* Pulse width 1ms duty 1 / 5

● Electrical and optical characteristics ($T_a = 25^\circ\text{C}$)

Parameter	Symbol	Conditions	Red			Orange			Yellow			Green			Unit
			Min.	Typ.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.	
Forward voltage	V_F	$I_F=10\text{mA}$	—	2.0	2.8	—	2.0	2.8	—	2.1	2.8	—	2.1	2.8	V
Reverse current	I_R	$V_R=5\text{V}$	—	—	100	—	—	100	—	—	100	—	—	100	μA
Peak wavelength	λ_P	$I_F=10\text{mA}$	—	650	—	—	610	—	—	585	—	—	563	—	nm
Spectral line half width	$\Delta\lambda$	$I_F=10\text{mA}$	—	40	—	—	40	—	—	40	—	—	40	—	nm

©Not designed for radiation resistance.

● Luminous intensity

Color	λ_P	Type	Min.	Typ.	Max.	Unit
Red	650	LA-6760	3.6	10	—	mcd
		LA-6780				
Orange	610	LA-6660	3.6	10	—	mcd
		LA-6680				
Yellow	585	LA-6860	3.6	10	—	mcd
		LA-6880				
Green	563	LA-6460	9	25	—	mcd
		LA-6480				

Note: Measured at $I_F = 10\text{mA}$