

M/A-COM Three-Way In-Phase Power Divider 25 - 1000 MHz

Features

- Space Qualified version of DS-323
- Designed to meet the Stringent Reliability Standards of Space Hardware
- 50 Ohms Nominal Impedance
- 35 dB Midband Isolation
- 1.2:1 Input VSWR

Description


M/A-COM's PD20-0010-S is a Three-Way Power Divider designed to operate over a frequency of 25 - 1000 MHz.

Absolute Maximum Ratings¹

Parameter	Absolute Maximum
Max. Input Power	1 Watt
Operating Temperature	-30°C to +85°C
Storage Temperature	-65°C to +125°C

1. Operation of this device above any one of these parameters may cause permanent damage.

FP-3



Electrical Specifications, T_A = +25°C

Parameter	Test Conditions	Frequency	Units	Min.	Max.
Insertion Loss	-	25-200 MHz	dB	-	0.5
		200-1000 MHz	dB	-	1.0
Isolation	-	25-49 MHz	dB	15	-
		50-199 MHz	dB	22	-
		200-1000 MHz	dB	24	-
Amplitude Balance	-	25-200 MHz	dB	-	0.25
		201-1000 MHz	dB	-	0.4
Phase Balance	-	25-200 MHz	-	-	2°
		201-1000 MHz	-	-	4°
VSWR	Input	25-1000 MHz	-	-	1.5
		25-49 MHz	-	-	2.2
		50-199 MHz	-	-	1.7:1
		200-1000 MHz	-	-	1.5:1

Specifications subject to change without notice.

V.2.0

- North America: Tel. (800) 366-2266, Fax (800) 618-8883
- Asia/Pacific: Tel.+81-44-844-8296, Fax +81-44-844-8298
- Europe: Tel. +44 (1344) 869 595, Fax+44 (1344) 300 020

tyco / Electronics

M/A-COM

Visit www.macom.com for additional data sheets and product information.