

## SGS10N60RUF-D

### Short Circuit Rated IGBT

#### General Description



Fairchild's RUF-D series of Insulated Gate Bipolar Transistors (IGBTs) provide low conduction and switching losses as well as short circuit ruggedness. The RUF-D series is designed for applications such as motor control, uninterrupted power supplies (UPS) and general inverters where short circuit ruggedness is a required feature.

#### Features

- Short circuit rated 10us @  $T_C = 100^\circ\text{C}$ ,  $V_{GE} = 15\text{V}$
- High speed switching
- Low saturation voltage :  $V_{CE(\text{sat})} = 2.2\text{V}$  @  $I_C = 10\text{A}$
- High input impedance
- CO-PAK, IGBT with FRD :  $t_{rr} = 42\text{ns}$  (typ.)

#### Application

AC & DC Motor controls, general purpose inverters, robotics, servo controls



#### Absolute Maximum Ratings $T_C = 25^\circ\text{C}$ unless otherwise noted

Symbol	Description	SGS10N60RUF-D	Units
$V_{CES}$	Collector-Emitter Voltage	600	V
$V_{GES}$	Gate-Emitter Voltage	$\pm 20$	V
$I_C$	Collector Current @ $T_C = 25^\circ\text{C}$	16	A
	Collector Current @ $T_C = 100^\circ\text{C}$	10	A
$I_{CM(1)}$	Pulsed Collector Current	30	A
$I_F$	Diode Continuous Forward Current @ $T_C = 100^\circ\text{C}$	12	A
$I_{FM}$	Diode Maximum Forward Current	92	A
$T_{SC}$	Short Circuit Withstand Time @ $T_C = 100^\circ\text{C}$	10	$\mu\text{s}$
$P_D$	Maximum Power Dissipation @ $T_C = 25^\circ\text{C}$	55	W
	Maximum Power Dissipation @ $T_C = 100^\circ\text{C}$	22	W
$T_J$	Operating Junction Temperature	-55 to +150	$^\circ\text{C}$
$T_{stg}$	Storage Temperature Range	-55 to +150	$^\circ\text{C}$
$T_L$	Maximum Lead Temp. for soldering purposes, 1/8" from case for 5 seconds	300	$^\circ\text{C}$

**Notes :**

(1) Repetitive rating : Pulse width limited by max. junction temperature

#### Thermal Characteristics

Symbol	Parameter	Typ.	Max.	Units
$R_{\theta JC}$ (IGBT)	Thermal Resistance, Junction-to-Case	--	2.3	$^\circ\text{C/W}$
$R_{\theta JC}$ (DIODE)	Thermal Resistance, Junction-to-Case	--	3.7	$^\circ\text{C/W}$
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient	--	62.5	$^\circ\text{C/W}$

### Electrical Characteristics of IGBT T<sub>C</sub> = 25°C unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
<b>Off Characteristics</b>						
BV <sub>CES</sub>	Collector-Emitter Breakdown Voltage	V <sub>GE</sub> = 0V, I <sub>C</sub> = 250uA	600	--	--	V
ΔBV <sub>CES</sub> /ΔT <sub>J</sub>	Temperature Coeff. of Breakdown Voltage	V <sub>GE</sub> = 0V, I <sub>C</sub> = 1mA	--	0.6	--	V/°C
I <sub>CES</sub>	Collector Cut-off Current	V <sub>CE</sub> = V <sub>CES</sub> , V <sub>GE</sub> = 0V	--	--	250	μA
I <sub>GES</sub>	G-E Leakage Current	V <sub>GE</sub> = V <sub>GES</sub> , V <sub>CE</sub> = 0V	--	--	± 100	nA

### On Characteristics

V <sub>GE(th)</sub>	G-E Threshold Voltage	I <sub>C</sub> = 10mA, V <sub>CE</sub> = V <sub>GE</sub>	5.0	6.0	8.5	V
V <sub>CE(sat)</sub>	Collector to Emitter Saturation Voltage	I <sub>C</sub> = 10A, V <sub>GE</sub> = 15V	--	2.2	2.8	V
		I <sub>C</sub> = 16A, V <sub>GE</sub> = 15V	--	2.5	--	V

### Dynamic Characteristics

C <sub>ies</sub>	Input Capacitance	V <sub>CE</sub> = 30V, V <sub>GE</sub> = 0V, f = 1MHz	--	660	--	pF
C <sub>oes</sub>	Output Capacitance		--	115	--	pF
C <sub>res</sub>	Reverse Transfer Capacitance		--	25	--	pF

### Switching Characteristics

t <sub>d(on)</sub>	Turn-On Delay Time	V <sub>CC</sub> = 300 V, I <sub>C</sub> = 10A, R <sub>G</sub> = 20Ω, V <sub>GE</sub> = 15V, Inductive Load, T <sub>C</sub> = 25°C	--	15	--	ns
t <sub>r</sub>	Rise Time		--	30	--	ns
t <sub>d(off)</sub>	Turn-Off Delay Time		--	36	50	nS
t <sub>f</sub>	Fall Time		--	158	200	ns
E <sub>on</sub>	Turn-On Switching Loss		--	141	--	μJ
E <sub>off</sub>	Turn-Off Switching Loss		--	215	--	μJ
E <sub>ts</sub>	Total Switching Loss	--	356	500	μJ	
t <sub>d(on)</sub>	Turn-On Delay Time	V <sub>CC</sub> = 300 V, I <sub>C</sub> = 10A, R <sub>G</sub> = 20Ω, V <sub>GE</sub> = 15V, Inductive Load, T <sub>C</sub> = 125°C	--	16	--	ns
t <sub>r</sub>	Rise Time		--	33	--	ns
t <sub>d(off)</sub>	Turn-Off Delay Time		--	42	60	ns
t <sub>f</sub>	Fall Time		--	242	350	ns
E <sub>on</sub>	Turn-On Switching Loss		--	161	--	μJ
E <sub>off</sub>	Turn-Off Switching Loss		--	452	--	μJ
E <sub>ts</sub>	Total Switching Loss	--	613	860	μJ	
T <sub>sc</sub>	Short Circuit Withstand Time	V <sub>CC</sub> = 300 V, V <sub>GE</sub> = 15V @ T <sub>C</sub> = 100°C	10	--	--	μs
Q <sub>g</sub>	Total Gate Charge	V <sub>CE</sub> = 300 V, I <sub>C</sub> = 10A, V <sub>GE</sub> = 15V	--	30	45	nC
Q <sub>ge</sub>	Gate-Emitter Charge		--	5	10	nC
Q <sub>gc</sub>	Gate-Collector Charge		--	8	16	nC
Le	Internal Emitter Inductance	Measured 5mm from PKG	--	7.5	--	nH

### Electrical Characteristics of DIODE T<sub>C</sub> = 25°C unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units	
V <sub>FM</sub>	Diode Forward Voltage	I <sub>F</sub> = 12A	T <sub>C</sub> = 25°C	--	1.4	1.7	V
			T <sub>C</sub> = 100°C	--	1.3	--	
t <sub>rr</sub>	Diode Reverse Recovery Time	I <sub>F</sub> = 12A, di/dt = 200A/μs	T <sub>C</sub> = 25°C	--	42	60	ns
			T <sub>C</sub> = 100°C	--	60	--	
I <sub>rr</sub>	Diode Peak Reverse Recovery Current	I <sub>F</sub> = 12A, di/dt = 200A/μs	T <sub>C</sub> = 25°C	--	3.5	6.0	A
			T <sub>C</sub> = 100°C	--	5.6	--	
Q <sub>rr</sub>	Diode Reverse Recovery Charge	I <sub>F</sub> = 12A, di/dt = 200A/μs	T <sub>C</sub> = 25°C	--	80	180	nC
			T <sub>C</sub> = 100°C	--	220	--	




Fig 1. Typical Output Characteristics




Fig 2. Typical Saturation Voltage Characteristics




Fig 3. Saturation Voltage vs. Case Temperature at Variant Current Level




Fig 4. Load Current vs. Frequency




Fig 5. Saturation Voltage vs.  $V_{GE}$







Fig 6. Saturation Voltage vs.  $V_{GE}$




**Fig 7. Capacitance Characteristics**




**Fig 8. Turn-On Characteristics vs. Gate Resistance**




**Fig 9. Turn-Off Characteristics vs. Gate Resistance**



**Fig 10. Switching Loss vs. Gate Resistance**



**Fig 11. Turn-On Characteristics vs. Collector Current**



**Fig 12. Turn-Off Characteristics vs. Collector Current**




Fig 13. Switching Loss vs. Collector Current




Fig 14. Gate Charge Characteristics




Fig 15. SOA Characteristics




Fig 16. Turn-Off SOA Characteristics




Fig 17. Transient Thermal Impedance of IGBT




Fig 18. Forward Characteristics




Fig 19. Reverse Recovery Current




Fig 20. Stored Charge





Fig 21. Reverse Recovery Time

Package Dimension

TO-220F (FS PKG CODE AQ)



Dimensions in Millimeters

## TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACE <sub>x</sub> <sup>™</sup>	FAST <sup>®</sup>	PACMAN <sup>™</sup>	SuperSOT <sup>™</sup> -3
Bottomless <sup>™</sup>	FAST <sub>r</sub> <sup>™</sup>	POP <sup>™</sup>	SuperSOT <sup>™</sup> -6
CoolFET <sup>™</sup>	GlobalOptoisolator <sup>™</sup>	PowerTrench <sup>®</sup>	SuperSOT <sup>™</sup> -8
CROSSVOLT <sup>™</sup>	GTO <sup>™</sup>	QFET <sup>™</sup>	SyncFET <sup>™</sup>
DenseTrench <sup>™</sup>	HiSeC <sup>™</sup>	QS <sup>™</sup>	TinyLogic <sup>™</sup>
DOME <sup>™</sup>	ISOPLANAR <sup>™</sup>	QT Optoelectronics <sup>™</sup>	UHC <sup>™</sup>
EcoSPARK <sup>™</sup>	LittleFET <sup>™</sup>	Quiet Series <sup>™</sup>	UltraFET <sup>®</sup>
E <sup>2</sup> C <sub>MOS</sub> <sup>™</sup>	MicroFET <sup>™</sup>	SLIENT SWITCHER <sup>®</sup>	VCX <sup>™</sup>
EnSigna <sup>™</sup>	MICROWIRE <sup>™</sup>	SMART START <sup>™</sup>	
FACT <sup>™</sup>	OPTOLOGIC <sup>™</sup>	Star* Power <sup>™</sup>	
FACT Quiet Series <sup>™</sup>	OPTOPLANAR <sup>™</sup>	Stealth <sup>™</sup>	

## DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

## PRODUCT STATUS DEFINITIONS

### Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.