

SHINDENGEN


Schottky Rectifiers (SBD)

Dual

SF15SC6

60V 15A

OUTLINE DIMENSIONS



RATINGS


● Absolute Maximum Ratings (Unless otherwise specified, $T_c=25^\circ\text{C}$)

Item	Symbol	Conditions	Ratings	Unit
Storage Temperature	T_{stg}		-55 ~ 150	$^\circ\text{C}$
Operating Junction Temperature	T_j		150	$^\circ\text{C}$
Maximum Reverse Voltage	V_{RM}		60	V
Repetitive Peak Surge Reverse Voltage	V_{RRSM}	Pulse width 0.5ms, duty 1/40	65	V
Average Rectified Forward Current	I_O	50Hz sine wave, R-load, Rating for each diode $I_o/2$, $T_c=122^\circ\text{C}$	15	A
Peak Surge Forward Current	I_{FSM}	50Hz sine wave, Non-repetitive 1 cycle peak value, $T_j=25^\circ\text{C}$	160	A
Repetitive Peak Surge Reverse Power	P_{RRSM}	Pulse width 10 μ s, Rating of per diode, $T_j=25^\circ\text{C}$	330	W
Dielectric Strength	V_{dis}	Terminals to case, AC 1 minute	2	kV
Mounting Torque	TOR	(Recommended torque: 0.3N·m)	0.5	N·m


● Electrical Characteristics (Unless otherwise specified, $T_c=25^\circ\text{C}$)

Item	Symbol	Conditions	Ratings	Unit
Forward Voltage	V_F	$I_F=7.5\text{A}$, Pulse measurement, Rating of per diode	Max 0.63	V
Reverse Current	I_R	$V_R=V_{RM}$, Pulse measurement, Rating of per diode	Max 6.0	mA
Junction Capacitance	C_j	$f=1\text{MHz}$, $V_R=10\text{V}$, Rating of per diode	Typ 260	pF
Thermal Resistance	θ_{jc}	junction to case	Max 2.0	$^\circ\text{C}/\text{W}$
	θ_{jf}	junction to heatsink	Max 4.5	$^\circ\text{C}/\text{W}$
	θ_{cf}	case to heatsink	Max 2.5	$^\circ\text{C}/\text{W}$


SF15SC6 Forward Voltage




SF15SC6 Reverse Current



SF15SC6 Forward Power Dissipation




$T_j = 150^\circ\text{C}$




SF15SC6

Reverse Power Dissipation




$T_j = 150^\circ\text{C}$




SF15SC6

Derating Curve




$V_R = 30V$



SF15SC6

Peak Surge Forward Capability



SF15SC6 Junction Capacitance

