

MC3242A



MEMORY ADDRESS MULTIPLEXER FOR 16K RAMS


The Motorola MC3242A is an address multiplexer and refresh counter for 16-pin 16K dynamic RAMs that require a 128-cycle refresh. It multiplexes fourteen system address bits to the seven address pins of the memory device. The MC3242A also contains a 7-bit refresh counter that is clocked externally to generate the 128 sequential addresses required for refresh. The high performance of the MC3242A will enhance the high speed of the N-channel RAMs such as the MCM4116.

- Simplifies 16-Pin 16K Dynamic Memory Design
- Reduces Package Count
- 7-Bit Binary Counter for 128 Refresh Address
- Multiplexing: Row Address/Column Address/Refresh Address
- High Input Impedance for Minimum Loading of Bus:
 - $I_F = 0.25 \text{ mA Max}$
- Schottky TTL for High Performance Address Input to Output Delay –
 - $t_{AO} = 25 \text{ ns @ } C_L = 250 \text{ pF}$
- Second Source to Intel 3242
(Detect Zero Function Not Included and Additional Chip Enable Feature Added at Pin 15)


7

MEMORY ADDRESS MULTIPLEXER AND REFRESH ADDRESS COUNTER


SCHOTTKY SILICON MONOLITHIC INTEGRATED CIRCUITS



L SUFFIX CERAMIC PACKAGE CASE 733-03



P SUFFIX PLASTIC PACKAGE CASE 710-02



Count	1	28	VCC
Ref En	2	27	A6
Row En	3	26	A13
N.C.	4	25	A5
A1	5	24	A12
A8	6	23	A4
A2	7	22	A11
A9	8	21	A3
A0	9	20	A10
A7	10	19	O6
O0	11	18	O3
O2	12	17	O4
O1	13	16	O5
Gnd	14	15	CE*

Note: A0 Through A6 Are Row Addresses
A7 Through A13 Are Column Addresses
*See Pin Definitions

TRUTH TABLE AND DEFINITIONS

Refresh Enable	Row Enable	Output
H	X	Refresh Address (From Internal Counter)
L	H	Row Address (A0 through A6)
L	L	Column Address (A7 through A13)

Count – Advances Internal Refresh Counter

ORDERING INFORMATION

Device	Temperature Range	Package
MC3242AL	0 to 75°C	Ceramic DIP
MC3242AP	0 to 75°C	Plastic DIP

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted.)

Rating	Symbol	Value	Unit
Power Supply Voltage	V_{CC}	-0.5 to +7.0	V
Input Voltage	V_I	-0.5 to +7.0	V
Output Voltage	V_O	-0.5 to +7.0	V
Output Current	I_O	100	mA
Operating Ambient Temperature	T_A	0 to +75	$^\circ\text{C}$
Storage Temperature	T_{stg}	-65 to +150	$^\circ\text{C}$
Junction Temperature	T_J	+175	$^\circ\text{C}$
Ceramic Package		+150	
Plastic Package			

“Absolute Maximum Ratings” are those values beyond which the safety of the device cannot be guaranteed. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum ratings for extended periods may affect reliability.

ELECTRICAL CHARACTERISTICS (Unless otherwise noted, Min/Max values apply with $4.5\text{ V} \leq V_{CC} \leq 5.5\text{ V}$, $0^\circ\text{C} \leq T_A \leq 75^\circ\text{C}$; typical values apply with $V_{CC} = 5.0\text{ V}$, $T_A = 25^\circ\text{C}$.)

Characteristic	Symbol	Min	Typ	Max	Unit
Input Current, Low Logic State ($V_{IL} = 0.45\text{ V}$)	I_{IL}	—	-0.25	-0.40	mA
Input Current, High Logic State ($V_{IH} = 5.5\text{ V}$)	I_{IH}	—	—	10	μA
Input Voltage, Low Logic State	V_{IL}	—	—	0.8	V
Input Voltage, High Logic State	V_{IH}	2.0	—	—	V
Output Voltage, Low Logic State ($I_{OL} = 5.0\text{ mA}$)	V_{OL}	—	0.25	0.4	V
Output Voltage, High Logic State ($I_{OH} = -1.0\text{ mA}$)	V_{OH}	3.0	4.0	—	V
Input Clamp Voltage ($I_{IK} = -12\text{ mA}$)	V_{IK}	—	-0.8	-1.5	V
Power Supply Current ($V_{CC} = 5.5\text{ V}$)	I_{CC}	—	80	125	mA

SWITCHING CHARACTERISTICS (Unless otherwise noted, Min/Max values apply with $4.5\text{ V} \leq V_{CC} \leq 5.5\text{ V}$, $0^\circ\text{C} \leq T_A \leq 75^\circ\text{C}$; typical values apply with $V_{CC} = 5.0\text{ V}$, $T_A = 25^\circ\text{C}$.)

Characteristic	Symbol	Min	Typ	Max	Unit
Propagation Delay Times					
Address Input to Output (Load = 1 TTL, $C_L = 250\text{ pF}$) (Load = 1 TTL, $C_L = 15\text{ pF}$, $V_{CC} = 5.0\text{ V}$, $T_A = 25^\circ\text{C}$)	t_{AO}	—	12 6.0	25 9.0	ns
Row Enable to Output (Load = 1 TTL, $C_L = 250\text{ pF}$) (Load = 1 TTL, $C_L = 15\text{ pF}$, $V_{CC} = 5.0\text{ V}$, $T_A = 25^\circ\text{C}$)	t_{OO}	12 7	27 12	41 27	ns
Refresh Enable to Output (Load = 1 TTL, $C_L = 250\text{ pF}$) (Load = 1 TTL, $C_L = 15\text{ pF}$, $V_{CC} = 5.0\text{ V}$, $T_A = 25^\circ\text{C}$)	t_{EO}	12 7	30 14	45 27	ns
Count Pulse Width	t_{WC}	30	—	—	ns
Counting Frequency	f_C	5.0	10	—	MHz

FIGURE 1 - AC WAVEFORMS WITH MCM4116 NORMAL CYCLE





FIGURE 2 - REFRESH CYCLE



7

TYPICAL CHARACTERISTICS

FIGURE 3 - OUTPUT CURRENT versus OUTPUT LOW VOLTAGE





FIGURE 4 - PROPAGATION DELAY versus LOAD CAPACITANCE Row or Column Address to Output



PIN DEFINITIONS

Count Input – Pin 1

Active low input increments internal 6-bit counter by one for each count pulse in.

Refresh Enable Input – Pin 2

Active high input which determines whether the MC3242A is in refresh mode (H) or address enable (L).

A0–A6 Inputs – Pins 9, 5, 7, 21, 23, 27

Row address inputs.

A7–A13 Inputs – Pins 10, 6, 8, 20, 22, 24, 26

Column address inputs.

$\overline{O0}$ – $\overline{O6}$ Outputs – Pins 11, 12, 13, 18, 17, 16, 19

Address outputs to memories. Inverted with respect to address inputs.

Gnd – Pin 14


Power supply ground.

CE Input – Pin 15

Optional use, chip enable control pin. Left open, an internal 50 k Ω pullup resistor keeps this pin high and the MC3242A is a functional replacement for the Intel 3242 (without detect zero function). As an active input, when pulled low, all 3242A outputs go three-state.


V_{CC} – Pin 28

+5 V power supply input. Due to high capacitance drive capability, a 0.1 μ F capacitor should be used to ground along with careful V_{CC} and Gnd Bus layout.



TYPICAL APPLICATION
16K X 8-BIT MEMORY SYSTEM FOR M6800

Note: Numbers in parenthesis indicate part types or values for 16K x 1 RAMs



7