






Zener Diodes

(Continued)

POWER	5.0 WATT		10 WATT	50 WATT	
					
CASE	AX-5W	DO-201	DO-4**	TO-3**	DO-5**
ZENER VOLTAGE	INDUSTRY STANDARD	RECOMMENDED FOR NEW DESIGNS	GENERAL PURPOSE	GENERAL PURPOSE	GENERAL PURPOSE
30	1N5363B	CZ5363B	1N2989B	1N2823B †	1N3324B
33	1N5364B	CZ5364B	1N2990B	1N2824B †	1N3325B
36	1N5365B	CZ5365B	1N2991B	1N2825B †	1N3326B
39	1N5366B	CZ5366B	1N2992B	1N2826B †	1N3327B
43	1N5367B	CZ5367B	1N2993B	1N2827B †	1N3328B
45			1N2994B	1N2828B †	1N3329B
47	1N5368B	CZ5368B	1N2995B	1N2829B †	1N3330B
50			1N2996B	1N2830B †	1N3331B
51	1N5369B	CZ5369B	1N2997B	1N2831B †	1N3332B
52			1N2998B		1N3333B
56	1N5370B	CZ5370B	1N2999B	1N2832B †	1N3334B
60	1N5371B*	CZ5371B			
62	1N5372B	CZ5372B	1N3000B	1N2833B †	1N3335B
68	1N5373B	CZ5373B	1N3001B	1N2834B †	1N3336B
75	1N5374B	CZ5374B	1N3002B	1N2835B †	1N3337B
82	1N5375B	CZ5375B	1N3003B	1N2836B †	1N3338B
87	1N5376B*	CZ5376B			
91	1N5377B	CZ5377B	1N3004B	1N2837B †	1N3339B
100	1N5378B	CZ5378B	1N3005B	1N2838B †	1N3340B
105			1N3006B	1N2839B †	1N3341B
110	1N5379B		1N3007B	1N2840B †	1N3342B
120	1N5380B	CZ5379B	1N3008B	1N2841B †	1N3343B
130	1N5381B	CZ5380B	1N3009B	1N2842B †	1N3344B
140	1N5382B*	CZ5381B	1N3010B		1N3345B
150	1N5383B	CZ5382B	1N3011B	1N2843B †	1N3346B
160	1N5384B	CZ5383B	1N3012B	1N2844B †	1N3347B
170	1N5385B*	CZ5385B	1N3013B		
175					1N3348B
180	1N5386B	CZ5386B	1N3014B	1N2845B †	1N3349B
190	1N5387B*	CZ5387B			
200	1N5388B	CZ5388B	1N3015B	1N2846B †	1N3350B

For complete specifications, please consult factory.

** Reverse polarity available. Simply change "B" suffix to "RB".

* Not recommended for new designs.

† Uses 60 mil leads.

See mechanical specifications on page 209

This datasheet has been download from:

www.datasheetcatalog.com

Datasheets for electronics components.