

TOSHIBA TRANSISTOR SILICON NPN EPITAXIAL PLANAR TYPE

2SC5255

VHF~UHF BAND LOW NOISE AMPLIFIER APPLICATIONS



Unit in mm

- Low Noise Figure : NF=1.5dB (f=2GHz)
- High Gain : Gain=8.5dB (f=2GHz)

MAXIMUM RATINGS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Collector-Base Voltage	V _{CB0}	15	V
Collector-Emitter Voltage	V _{CEO}	7	V
Emitter-Base Voltage	V _{EB0}	1.5	V
Collector Current	I _C	40	mA
Base Current	I _B	20	mA
Collector Power Dissipation	P _C	100	mW
Junction Temperature	T _j	125	°C
Storage Temperature Range	T _{stg}	-55~125	°C

MARKING



MICROWAVE CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Transition Frequency	f _T	V _{CE} =5V, I _C =20mA	9	12	—	GHz
Insertion Gain	S _{21e} ² (1)	V _{CE} =5V, I _C =20mA, f=1GHz	11.5	14.5	—	dB
	S _{21e} ² (2)	V _{CE} =5V, I _C =20mA, f=2GHz	5.5	8.5	—	
Noise Figure	NF (1)	V _{CE} =5V, I _C =5mA, f=1GHz	—	1.1	—	dB
	NF (2)	V _{CE} =5V, I _C =5mA, f=2GHz	—	1.5	3	

ELECTRICAL CHARACTERISTICS (Ta = 25°C)







CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Collector Cut-off Current	I _{CBO}	V _{CB} =10V, I _E =0	—	—	1	μA
Emitter Cut-off Current	I _{EBO}	V _{EB} =1V, I _C =0	—	—	1	μA
DC Current Gain	h _{FE} (Note 1)	V _{CE} =5V, I _C =20mA	50	—	160	—
Output Capacitance	C _{ob}	V _{CB} =5V, I _E =0, f=1MHz (Note 2)	—	0.5	—	pF
Reverse Transfer Capacitance	C _{re}		—	0.4	0.8	pF

(Note 1) : h_{FE} Classification R : 50~100, O : 80~160

(Note 2) : C_{re} is measured by 3 terminal method with capacitance bridge.



961001EAA2

● TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.



961001EAA2'

- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.



S-PARAMETER $Z_o = 50\Omega$, $T_a = 25^\circ\text{C}$
 $V_{CE} = 5\text{V}$, $I_C = 5\text{mA}$

FREQUENCY (MHz)	S11		S21		S12		S22	
	Mag.	Ang.	Mag.	Ang.	Mag.	Ang.	Mag.	Ang.
200	0.739	-36.1	11.765	147.6	0.041	74.9	0.866	-25.5
400	0.579	-64	9.129	125.5	0.069	67.8	0.701	-41.9
600	0.454	-84.9	7.039	111	0.09	66.2	0.581	-51.6
800	0.375	-102.5	5.703	100.4	0.11	66.5	0.501	-58.5
1000	0.316	-116.3	4.713	92.5	0.128	67	0.442	-64.8
1200	0.272	-130.2	4.022	85.8	0.147	67.4	0.398	-70
1400	0.247	-144.6	3.492	80	0.166	68.2	0.361	-74.8
1600	0.216	-158.8	3.094	75.4	0.186	68.3	0.332	-78.8
1800	0.194	-173	2.765	71.1	0.208	68.5	0.308	-82.1
2000	0.173	175.4	2.508	67	0.228	68.6	0.288	-84

$V_{CE} = 5\text{V}$, $I_C = 20\text{mA}$

FREQUENCY (MHz)	S11		S21		S12		S22	
	Mag.	Ang.	Mag.	Ang.	Mag.	Ang.	Mag.	Ang.
200	0.407	-61.6	18.832	126.4	0.031	73.9	0.671	-34.0
400	0.271	-92.4	11.34	106.5	0.053	74.7	0.496	-41.9
600	0.211	-113.2	7.947	96.4	0.075	76.6	0.425	-45.8
800	0.19	-131.4	6.139	89.3	0.097	77.3	0.386	-50.1
1000	0.179	-146.5	4.975	83.6	0.12	77.3	0.355	-55.2
1200	0.172	-164	4.193	78.6	0.142	77	0.331	-59.8
1400	0.169	-175.6	3.627	74.3	0.166	76.5	0.311	-64.3
1600	0.165	168.7	3.215	70.4	0.189	76	0.292	-68.2
1800	0.16	155.5	2.866	66.7	0.213	75.2	0.278	-71.1
2000	0.157	143.6	2.587	63.4	0.236	74.2	0.267	-72.7