


# SBD Type :11EQS06

## FEATURES

- \* Miniature Size
- \* Low Forward Voltage Drop
- \* High Surge Capability
- \* 30volts through 100volts Types Available
- \* 26mm and 52mm Inside Tape Spacing Package Available

## OUTLINE DRAWING



## Maximum Ratings

Approx Net Weight:0.17g

Rating	Symbol	11EQS06				Unit				
Repetitive Peak Reverse Voltage	V <sub>RRM</sub>	60				V				
Non-repetitive Peak Reverse Voltage	V <sub>RSM</sub>	65				V				
Average Rectified Output Current	Without Fin or P.C.Board	Io	0.8	T <sub>a</sub> =28°C	Half Sine Wave Resistive Load	A				
	P.C.Board Mounted *		1.0	T <sub>a</sub> =29°C						
RMS Forward Current	I <sub>F(RMS)</sub>	1.57				A				
Surge Forward Current	I <sub>FSM</sub>	25	Half Sine Wave, 1cycle, Non-repetitive			A				
Operating Junction Temperature Range	T <sub>jw</sub>	- 40 to + 150				°C				
Storage Temperature Range	T <sub>stg</sub>	- 40 to + 150				°C				

## Electrical • Thermal Characteristics

Characteristics	Symbol	Conditions	Min	Typ	Max	Unit
Peak Reverse Current	I <sub>RM</sub>	T <sub>j</sub> = 25°C, V <sub>RM</sub> = V <sub>RRM</sub>	-	-	1	mA
Peak Forward Voltage	V <sub>FM</sub>	T <sub>j</sub> = 25°C, I <sub>FM</sub> = 1 A	-	-	0.58	V
Thermal Resistance(Junction to Ambient)	R <sub>th(j-a)</sub>	Without Fin or P.C.Board	-	-	140	°C/W
		P.C.Board mounted *	-	-	110	

\* :Print Lands = 5x5 mm, Both Sides

11EQS06 OUTLINE DRAWING (Dimensions in mm)

