


Central Semiconductor Corp.

Central Semiconductor Corp.

Central Semiconductor Corp.

Central Semiconductor Corp.

145 Adams Avenue
Hauppauge, New York 11788



2N5632 2N5633 2N5634 NPN
2N6229 2N6230 2N6231 PNP

COMPLEMENTARY SILICON POWER
TRANSISTORS

JEDEC TO-3 CASE

DESCRIPTION

The CENTRAL SEMICONDUCTOR 2N5632, 2N6229 series types are complementary silicon power transistors manufactured by the epitaxial base process mounted in a hermetically sealed metal case designed for high power amplifier and switching applications where high voltages are required.

MAXIMUM RATINGS ($T_C=25^\circ\text{C}$ unless otherwise noted)

	SYMBOL	2N5632 2N6229	2N5633 2N6230	2N5634 2N6231	UNIT
Collector-Base Voltage	V_{CB0}	100	120	140	V
Collector-Emitter Voltage	V_{CE0}	100	120	140	V
Emitter-Base Voltage	V_{EB0}	7.0	7.0	7.0	V
Collector Current	I_C	10	10	10	A
Collector Current (Peak)	I_{CM}	15	15	15	A
Base Current	I_B	5.0	5.0	5.0	A
Power Dissipation	PD	150	150	150	W
Operating and Storage Junction Temperature	T_J, T_{STG}	-65 TO +200			$^\circ\text{C}$
Thermal Resistance	θ_{JC}	1.17			$^\circ\text{C}/\text{W}$

ELECTRICAL CHARACTERISTICS ($T_C=25^\circ\text{C}$ unless otherwise noted)

SYMBOL	TEST CONDITIONS	2N5632 2N6229		2N5633 2N6230		2N5634 2N6231		UNIT
		MIN	MAX	MIN	MAX	MIN	MAX	
I_{CB0}	$V_{CB}=\text{Rated } V_{CB0}$		1.0		1.0		1.0	mA
I_{CEV}	$V_{CE}=\text{Rated } V_{CB0}, V_{EB}(\text{OFF})=1.5\text{V}$		1.0		1.0		1.0	mA
I_{CEV}	$V_{CE}=\text{Rated } V_{CB0}, V_{EB}(\text{OFF})=1.5\text{V}, T_C=150^\circ\text{C}$		5.0		5.0		5.0	mA
I_{CE0}	$V_{CE}=\frac{1}{2} \text{ Rated } V_{CB0}$		1.0		1.0		1.0	mA
I_{EB0}	$V_{BE}=7.0\text{V}$		1.0		1.0		1.0	mA
BV_{CE0}	$I_C=200\text{mA}$	100		120		140		V
$V_{CE}(\text{SAT})$	$I_C=7.5\text{A}, I_B=0.75\text{A}$		1.0		1.0		1.0	V
$V_{CE}(\text{SAT})$	$I_C=10\text{A}, I_B=2.0\text{A}$		2.0		2.0		2.0	V
$V_{BE}(\text{SAT})$	$I_C=7.5\text{A}, I_B=0.75\text{A}$		2.0		2.0		2.0	V
$V_{BE}(\text{ON})$	$V_{CE}=2.0\text{V}, I_C=5.0\text{A}$		1.5		1.5		1.5	V
hFE	$V_{CE}=2.0\text{V}, I_C=5.0\text{A}$	25	100	20	80	15	60	
hFE	$V_{CE}=2.0\text{V}, I_C=10\text{A}$	5.0		5.0		5.0		
hfe	$V_{CE}=10\text{V}, I_C=2.0\text{A}, f=1.0\text{kHz}$	15		15		15		
f_T	$V_{CE}=20\text{V}, I_C=1.0\text{A}, f=0.5\text{MHz}$	1.0		1.0		1.0		MHz
C_{ob}	$V_{CB}=10\text{V}, I_E=0, f=0.1\text{MHz}$ (NPN types)		300		300		300	pF
C_{ob}	$V_{CB}=10\text{V}, I_E=0, f=0.1\text{MHz}$ (PNP types)		600		600		600	pF

CentralTM
Semiconductor Corp.

145 Adams Avenue
Hauppauge, NY 11788 USA
Tel: (631) 435-1110 • Fax: (631) 435-1824
www.centrasemi.com

This datasheet has been download from:

www.datasheetcatalog.com

Datasheets for electronics components.