




LOW VOLTAGE RECTIFIER Transformers with horizontal channel frames.

- Primary voltage, 115 Volts, 60 Hz.
- Primary and secondary leads 8-10" long.
- 2-hole horizontal mounting.
- 6 sizes are available, covering the range: 1 to 10 VA.
- CSA listed (LR 47366).



MECHANICAL



Dimensions, Inches

P/N	DIMENSIONS			PIN SPACING A
	L	W	H	
4760	2.06	1.25	1.19	1.75
4761	2.06	1.38	1.19	1.75
4762	2.38	1.38	1.38	2.00
4763	2.38	1.50	1.38	2.00
4764	2.81	1.88	1.69	2.38
4765	2.81	2.00	1.69	2.38

ELECTRICAL SPECIFICATION

Part No.	Secondary Voltages (A-A)		
	F.L. Volts	N.L. Volts	Current Amps
4760-01	5.0	6.11	0.250
4760-02	6.3	7.45	0.150
4761-01	14.0	17.50	0.150
4761-02	20.0	24.50	0.100
4762-01	5.0	5.83	0.500
4762-02	6.3	7.10	0.300
4762-03	6.3	7.80	0.600
4762-04	10.0	12.40	0.300
4762-05	12.6	15.70	0.300
4762-06	20.0	23.50	0.150
4762-07	25.0	28.80	0.100
4762-08	25.0	30.80	0.150
4762-09	50.0	62.00	0.075
4763-01	5.0	6.17	1.000
4763-02	7.0	8.30	0.700
4763-03	8.0	9.52	0.500
4763-04	9.0	10.90	0.500
4763-05	16.0	18.60	0.250
4763-06	30.0	37.40	0.150

Part No.	Secondary Voltages (A-A)		
	F.L. Volts	N.L. Volts	Current Amps
4764-01	6.3	7.10	1.000
4764-02	10.0	11.00	0.500
4764-03	12.6	14.50	0.500
4764-04	14.0	16.10	0.500
4764-05	20.0	22.80	0.300
4764-06	25.0	29.00	0.300
4764-07	30.0	36.10	0.250
4764-08	36.0	40.70	0.150
4764-09	44.0	51.60	0.150
4765-01	8.5	9.60	1.000
4765-02	16.0	18.00	0.500
4765-03	28.0	31.70	0.250