

TENTATIVE

TOSHIBA PHOTOCOUPLER GaAs IRED + PHOTO-TRIAC

**TLP762JF**

OFFICE MACHINE

HOUSEHOLD USE EQUIPMENT

TRIAC DRIVER

SOLID STATE RELAY

The TOSHIBA TLP762JF consists of a GaAs infrared LED optically coupled to a photo-triac in a 6 lead plastic DIP.

- Peak Off-State Voltage : 600V (MIN.)
- Trigger LED Current : 10mA (MAX.)
- On-State Current : 100mA (MAX.)
- UL Recognized : UL1577, File No. E67349
- BSI Approved : BS EN60065 : 1994,  
Certificate No. 7831  
BS EN60950 : 1992,  
Certificate No. 7832
- SEMKO Approved : SS-EN60065 (EN60065, 1993)  
SS-EN60950 (EN60950, 1992)  
SS-EN60335 (EN60335, 1988)  
Certificate No. 9522145
- Isolation Voltage : 4000Vrms (Min.)
- Option (D4) type VDE Approved : DIN VDE0884 / 06.92,  
Certificate No. 91803


Maximum Operating Insulation Voltage : 1130V<sub>PK</sub>

Highest Permissible Over Voltage : 6000V<sub>PK</sub>

(Note) When a VDE0884 approved type is needed,  
please designate the "Option (D4)"


- Creepage Distance : 8.0mm (Min.)
- Clearance : 8.0mm (Min.)
- Internal Creepage Path : 4.0mm (Min.)
- Insulation Thickness : 0.4mm (Min.)

Unit in mm



Weight : 0.42g

## PIN CONFIGURATION (TOP VIEW)



Please refer to the technical data of TLP762J for MAXIMUM RATINGS and ELECTRICAL CHARACTERISTICS.

961001EAA2

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.