

HFE4226

Next Generation High Power LEDs, Metal ST Package

ELECTRO-OPTICAL CHARACTERISTICS (T_A = -40 to +85°C unless otherwise specified)

PARAMETER	SYMBOL	MIN	TYP ⁽¹⁾	MAX	UNITS	TEST CONDITIONS
Fiber Coupled Power (HFE4226-X22) Peak, T _A =25°C Peak over temp.	P _{oc}	-17.3 -18.9	-13.8	-11.4 -10.8	dBm	I _F =100 mA Peak 50/125μm fiber, NA = 0.20
Fiber Coupled Power Peak, T _A =25°C Peak over temp.	P _{oc}	-18.8 -19.8	-15.8	-13.8 -12.8	dBm	I _F = 60 mA Peak 50/125 μm fiber, NA = 0.20
Fiber Coupled Power Peak, T _A =25°C Peak over temp.	P _{oc}	-13.5 -15.1	-10.0	-7.6 -7.0	dBm	I _F = 100 mA Peak 62.5/125 μm fiber, NA = 0.275
Fiber Coupled Power Peak, T _A =25°C Peak over temp.	P _{oc}	-15.0 -16.0	-12.0	-10.0 -9.0	dBm	I _F = 60 mA Peak 62.5/125 μm fiber, NA = 0.275
Fiber Coupled Power (HFE4226-X23) Peak, T _A =25°C Peak over temp.	P _{oc}	-15.0 -16.0	-10.5	-9.0 -8.0	dBm	I _F = 60 mA Peak 62.5/125 μm fiber, NA = 0.275
Forward Voltage	V _F		1.84		V	I _F = 100 mA
Forward Voltage Temperature Coefficient	$\Delta V_F/\Delta T$ $\Delta V_F/\Delta T$		-0.18 -0.22		mV/°C mV/°C	I _F = 60 mA I _F = 60 mA
Reverse Voltage	B _{VR}	1.8	3.8		V	I _R = 10 μA, T _A =25°C
Peak Wavelength	λ_P	810	856	895	nm	I _F = 100 mA DC
	λ_P	810	850	885	nm	I _F = 60 mA DC
Spectral Bandwidth (FWHM)			55		nm	I _F = 100 mA DC
			50		nm	I _F = 60 mA DC
Response Time	t _r /t _f		4.0	6.3	ns	I _F = 60 mA peak, No Prebias
P _o Temperature Coefficient	$\Delta P_o/\Delta T$ $\Delta P_o/\Delta T$		-0.017 -0.006		dB/°C dB/°C	I _F = 100 mA I _F = 60 mA
Series Resistance	r _s		4.0		Ω	DC
Device Capacitance	C		40		pF	V _R = 0 V, f = 1 MHz
Thermal Resistance			260		°C/W	Heat sinked

- Notes
1. Typical specifications are for operations at T_C= 25°C.
 2. P_{oc} is measured using a 10 meter mode stripped cable which is intended to accurately represent a working system.

ABSOLUTE MAXIMUM RATINGS

Storage temperature	-55 to +85°C
Case operating temperature	-40 to +85°C
Lead solder temperature	269°C, 10 s
Reverse voltage	1.8 V
Continuous forward current (heat sinked)	100 mA

Stresses greater than those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational section of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods of time may affect reliability.

Honeywell reserves the right to make changes in order to improve design and supply the best products possible.

4551830 0021803 427

Honeywell

99

HFE4226

Next Generation High Power LEDs, Metal ST Package

ORDER GUIDE

Description	Catalog Listing
Threaded metal barrel and housing, standard power	HFE4226-022
Threaded metal barrel and housing, crimped leads, standard power	HFE4226-422
Threaded metal barrel and housing, extended power	HFE4226-023
Threaded metal barrel and housing, crimped leads, extended power	HFE4226-423

WARNING

Under certain application conditions, the infrared optical output of this device may exceed Class 1 eye safety limits, as defined by IEC 825-1 (1993-11). Do not use magnification (such as a microscope or other focusing equipment) when viewing the device's output.

CAUTION

The inherent design of this component causes it to be sensitive to electrostatic discharge (ESD). To prevent ESD-induced damage and/or degradation to equipment, take normal ESD precautions when handling this product.



Fig. 1 Typical Optical Power Output vs Forward Current




Fig. 2 Typical Spectral Output vs Wavelength





Fig. 3 Typical Optical Power Output vs Case Temperature



All Performance Curves Show Typical Values

4551830 0021804 363

Honeywell

Honeywell reserves the right to make changes in order to improve design and supply the best products possible.