

HVC308A

Variable Capacitance Diode for TV tuner

HITACHI

Rev. 0
Nov. 1995


Features

- Low series resistance. ($r_s=0.95\Omega$ max)
- Ultra small Flat Package (UFP) is suitable for surface mount design.

Ordering Information

Type No.	Laser Mark	Package Code
HVC308A	V	UFP

Outline



Absolute Maximum Ratings ($T_a = 25^\circ\text{C}$)

Item	Symbol	Value	Unit
Reverse voltage	V_R	35	V
Junction temperature	T_j	125	$^\circ\text{C}$
Storage temperature	T_{stg}	-55 to +125	$^\circ\text{C}$

Electrical Characteristics ($T_a = 25^\circ\text{C}$)

Item	Symbol	Min	Typ	Max	Unit	Test Condition
Reverse current	I_{R1}	—	—	10	nA	$V_R = 30\text{ V}$
	I_{R2}	—	—	100		$V_R = 30\text{ V}$, $T_a = 60^\circ\text{C}$
Capacitance	C_2	13.7	—	15.9	pF	$V_R = 2\text{ V}$, $f = 1\text{ MHz}$
	C_{20}	1.65	—	2.06		$V_R = 20\text{ V}$, $f = 1\text{ MHz}$
Capacitance ratio	n	7.12	—	—	—	C_2 / C_{20}
Series resistance	r_s	—	—	0.95	Ω	$V_R = 5\text{ V}$, $f = 470\text{ MHz}$




Fig.1 Reverse current Vs. Reverse voltage




Fig.2 Capacitance Vs. Reverse voltage




Fig.3 Series resistance Vs. Reverse voltage





Fig.4 Linearity factor Vs. Reverse voltage

Package Dimensions

Unit: mm



- 1 Cathode
- 2 Anode

HITACHI Code	UFP
JEDEC Code	—
EIAJ Code	SC-79
Weight (g)	0.0016