

HVU350B

Variable Capacitance Diode for VCO

HITACHI

Rev. 0
Feb. 1996


Features

- High capacitance ratio. ($n = 2.8$.min)
- Low series resistance. ($r_s = 0.5\Omega$ max)
- Low series resistance and good C-V linearity.
- Ultra small Resin Package (URP) is suitable for surface mount design.

Ordering Information

Type No.	Laser Mark	Package Code
HVU350B	B0	URP

Outline



Absolute Maximum Ratings ($T_a = 25^\circ\text{C}$)

Item	Symbol	Value	Unit
Reverse voltage	V_R	15	V
Junction temperature	T_j	125	$^\circ\text{C}$
Storage temperature	T_{stg}	-55 to +125	$^\circ\text{C}$

Electrical Characteristics ($T_a = 25^\circ\text{C}$)

Item	Symbol	Min	Typ	Max	Unit	Test Condition
Reverse current	I_{R1}	—	—	10	nA	$V_R = 15\text{ V}$
	I_{R2}	—	—	100		$V_R = 15\text{ V}$, $T_a = 60^\circ\text{C}$
Capacitance	C_1	15.5	—	17.0	pF	$V_R = 1\text{ V}$, $f = 1\text{ MHz}$
	C_4	5.0	—	6.0		$V_R = 4\text{ V}$, $f = 1\text{ MHz}$
Capacitance ratio	n	2.8	—	—	—	C_1 / C_4
Series resistance	r_s	—	—	0.5	Ω	$V_R = 1\text{ V}$, $f = 470\text{ MHz}$




Fig.1 Reverse current Vs. Reverse voltage




Fig.2 Capacitance Vs. Reverse voltage




Fig.3 Series resistance Vs. Reverse voltage





Fig.4 Linearity factor Vs. Reverse voltage

Package Dimensions

Unit: mm



- 1 Cathode
- 2 Anode

HITACHI Code	URP
JEDEC Code	—
EIAJ Code	—
Weight (g)	0.004