

Designer's™ Data Sheet

Insulated Gate Bipolar Transistor

N-Channel Enhancement-Mode Silicon Gate



MGW12N120

Motorola Preferred Device

This Insulated Gate Bipolar Transistor (IGBT) uses an advanced termination scheme to provide an enhanced and reliable high voltage-blocking capability. Short circuit rated IGBT's are specifically suited for applications requiring a guaranteed short circuit withstand time such as Motor Control Drives. Fast switching characteristics result in efficient operation at high frequencies.

- Industry Standard High Power TO-247 Package with Isolated Mounting Hole
- High Speed E_{off} : 160 μ J/A typical at 125°C
- High Short Circuit Capability – 10 μ s minimum
- Robust High Voltage Termination

IGBT IN TO-247
12 A @ 90°C
20 A @ 25°C
1200 VOLTS
SHORT CIRCUIT RATED



CASE 340F-03, Style 4
TO-247AE

MAXIMUM RATINGS ($T_J = 25^\circ\text{C}$ unless otherwise noted)

Rating	Symbol	Value	Unit
Collector-Emitter Voltage	V_{CES}	1200	Vdc
Collector-Gate Voltage ($R_{GE} = 1.0 \text{ M}\Omega$)	V_{CGR}	1200	Vdc
Gate-Emitter Voltage — Continuous	V_{GE}	± 20	Vdc
Collector Current — Continuous @ $T_C = 25^\circ\text{C}$ — Continuous @ $T_C = 90^\circ\text{C}$ — Repetitive Pulsed Current (1)	I_{C25} I_{C90} I_{CM}	20 12 40	Adc Apk
Total Power Dissipation @ $T_C = 25^\circ\text{C}$ Derate above 25°C	P_D	123 0.98	Watts W/ $^\circ\text{C}$
Operating and Storage Junction Temperature Range	T_J, T_{stg}	-55 to 150	$^\circ\text{C}$
Short Circuit Withstand Time ($V_{CC} = 720 \text{ Vdc}$, $V_{GE} = 15 \text{ Vdc}$, $T_J = 125^\circ\text{C}$, $R_G = 20 \Omega$)	t_{sc}	10	μs
Thermal Resistance — Junction to Case – IGBT — Junction to Ambient	$R_{\theta JC}$ $R_{\theta JA}$	1.0 45	$^\circ\text{C/W}$
Maximum Lead Temperature for Soldering Purposes, 1/8" from case for 5 seconds	T_L	260	$^\circ\text{C}$
Mounting Torque, 6-32 or M3 screw	10 lbf•in (1.13 N•m)		

(1) Pulse width is limited by maximum junction temperature. Repetitive rating.

Designer's Data for "Worst Case" Conditions — The Designer's Data Sheet permits the design of most circuits entirely from the information presented. SOA Limit curves — representing boundaries on device characteristics — are given to facilitate "worst case" design.

Preferred devices are Motorola recommended choices for future use and best overall value.

MGW12N120

ELECTRICAL CHARACTERISTICS ($T_J = 25^\circ\text{C}$ unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS					
Collector-to-Emitter Breakdown Voltage ($V_{GE} = 0\text{ Vdc}$, $I_C = 25\text{ }\mu\text{Adc}$) Temperature Coefficient (Positive)	BV_{CES}	1200 —	— 870	— —	Vdc mV/ $^\circ\text{C}$
Emitter-to-Collector Breakdown Voltage ($V_{GE} = 0\text{ Vdc}$, $I_{EC} = 100\text{ mAdc}$)	BV_{ECS}	25	—	—	Vdc
Zero Gate Voltage Collector Current ($V_{CE} = 1200\text{ Vdc}$, $V_{GE} = 0\text{ Vdc}$) ($V_{CE} = 1200\text{ Vdc}$, $V_{GE} = 0\text{ Vdc}$, $T_J = 125^\circ\text{C}$)	I_{CES}	— —	— —	100 2500	μAdc
Gate-Body Leakage Current ($V_{GE} = \pm 20\text{ Vdc}$, $V_{CE} = 0\text{ Vdc}$)	I_{GES}	—	—	250	nAdc

ON CHARACTERISTICS (1)

Collector-to-Emitter On-State Voltage ($V_{GE} = 15\text{ Vdc}$, $I_C = 5.0\text{ Adc}$) ($V_{GE} = 15\text{ Vdc}$, $I_C = 5.0\text{ Adc}$, $T_J = 125^\circ\text{C}$) ($V_{GE} = 15\text{ Vdc}$, $I_C = 10\text{ Adc}$)	$V_{CE(on)}$	— — —	2.51 2.36 3.21	3.37 — 4.42	Vdc
Gate Threshold Voltage ($V_{CE} = V_{GE}$, $I_C = 1.0\text{ mAdc}$) Threshold Temperature Coefficient (Negative)	$V_{GE(th)}$	4.0 —	6.0 10	8.0 —	Vdc mV/ $^\circ\text{C}$
Forward Transconductance ($V_{CE} = 10\text{ Vdc}$, $I_C = 10\text{ Adc}$)	g_{fe}	—	12	—	Mhos

DYNAMIC CHARACTERISTICS

Input Capacitance	$(V_{CE} = 25\text{ Vdc}$, $V_{GE} = 0\text{ Vdc}$, $f = 1.0\text{ MHz}$)	C_{ies}	—	930	—	pF
Output Capacitance		C_{oes}	—	126	—	
Transfer Capacitance		C_{res}	—	16	—	

SWITCHING CHARACTERISTICS (1)

Turn-On Delay Time	$(V_{CC} = 720\text{ Vdc}$, $I_C = 10\text{ Adc}$, $V_{GE} = 15\text{ Vdc}$, $L = 300\text{ }\mu\text{H}$ $R_G = 20\text{ }\Omega$, $T_J = 25^\circ\text{C}$) Energy losses include "tail"	$t_{d(on)}$	—	74	—	ns
Rise Time		t_r	—	83	—	
Turn-Off Delay Time		$t_{d(off)}$	—	76	—	
Fall Time		t_f	—	231	—	
Turn-Off Switching Loss		E_{off}	—	0.55	1.33	mJ
Turn-On Delay Time	$(V_{CC} = 720\text{ Vdc}$, $I_C = 10\text{ Adc}$, $V_{GE} = 15\text{ Vdc}$, $L = 300\text{ }\mu\text{H}$ $R_G = 20\text{ }\Omega$, $T_J = 125^\circ\text{C}$) Energy losses include "tail"	$t_{d(on)}$	—	66	—	ns
Rise Time		t_r	—	87	—	
Turn-Off Delay Time		$t_{d(off)}$	—	120	—	
Fall Time		t_f	—	575	—	
Turn-Off Switching Loss		E_{off}	—	1.49	—	mJ
Gate Charge	$(V_{CC} = 720\text{ Vdc}$, $I_C = 10\text{ Adc}$, $V_{GE} = 15\text{ Vdc}$)	Q_T	—	31	—	nC
		Q_1	—	13	—	
		Q_2	—	14	—	

INTERNAL PACKAGE INDUCTANCE

Internal Emitter Inductance (Measured from the emitter lead 0.25" from package to emitter bond pad)	L_E	—	13	—	nH
--	-------	---	----	---	----

(1) Pulse Test: Pulse Width $\leq 300\text{ }\mu\text{s}$, Duty Cycle $\leq 2\%$.

TYPICAL ELECTRICAL CHARACTERISTICS




Figure 1. Output Characteristics, $T_J = 25^\circ\text{C}$




Figure 2. Output Characteristics, $T_J = 125^\circ\text{C}$




Figure 3. Transfer Characteristics




Figure 4. Collector-to-Emitter Saturation Voltage versus Junction Temperature




Figure 5. Capacitance Variation




Figure 6. Gate-to-Emitter Voltage versus Total Charge

MGW12N120




Figure 7. Total Switching Losses versus Gate Resistance




Figure 8. Total Switching Losses versus Case Temperature




Figure 9. Total Switching Losses versus Collector-to-Emitter Current




Figure 10. Maximum Forward Drop versus Instantaneous Forward Current




Figure 11. Reverse Biased Safe Operating Area






Figure 12. Thermal Response

PACKAGE DIMENSIONS



NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.

DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	20.40	20.90	0.803	0.823
B	15.44	15.95	0.608	0.628
C	4.70	5.21	0.185	0.205
D	1.09	1.30	0.043	0.051
E	1.50	1.63	0.059	0.064
F	1.80	2.18	0.071	0.086
G	5.45 BSC		0.215 BSC	
H	2.56	2.87	0.101	0.113
J	0.48	0.68	0.019	0.027
K	15.57	16.08	0.613	0.633
L	7.26	7.50	0.286	0.295
P	3.10	3.38	0.122	0.133
Q	3.50	3.70	0.138	0.145
R	3.30	3.80	0.130	0.150
U	5.30 BSC		0.209 BSC	
V	3.05	3.40	0.120	0.134

STYLE 4:

- PIN 1. GATE
- COLLECTOR
- EMITTER
- COLLECTOR

**CASE 340F-03
TO-247AE
ISSUE E**

Motorola reserves the right to make changes without further notice to any products herein. Motorola makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Motorola assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters which may be provided in Motorola data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Motorola does not convey any license under its patent rights nor the rights of others. Motorola products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Motorola product could create a situation where personal injury or death may occur. Should Buyer purchase or use Motorola products for any such unintended or unauthorized application, Buyer shall indemnify and hold Motorola and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Motorola was negligent regarding the design or manufacture of the part. Motorola and  are registered trademarks of Motorola, Inc. Motorola, Inc. is an Equal Opportunity/Affirmative Action Employer.

How to reach us:

USA/EUROPE/Locations Not Listed: Motorola Literature Distribution;
P.O. Box 20912; Phoenix, Arizona 85036. 1-800-441-2447 or 602-303-5454

MFAX: RMFAX0@email.sps.mot.com – TOUCHTONE 602-244-6609
INTERNET: <http://Design-NET.com>

JAPAN: Nippon Motorola Ltd.; Tatsumi-SPD-JLDC, 6F Seibu-Butsuryu-Center,
3-14-2 Tatsumi Koto-Ku, Tokyo 135, Japan. 03-81-3521-8315

ASIA/PACIFIC: Motorola Semiconductors H.K. Ltd.; 8B Tai Ping Industrial Park,
51 Ting Kok Road, Tai Po, N.T., Hong Kong. 852-26629298

