

- ◆ High Power Handling
- ◆ Small Capacitance at Zero Bias, Extremely Small Reverse Bias
- ◆ Small Series Order Resistance
- ◆ Small Insertion Loss, High Isolation
- ◆ Extremely Small Wave Distortion
(TX spurious < -80dBc, RX intermodulation = -73dBc at 90dB μ)


General Description

The XB15A308 PIN diode employs a high reliability glass package that is designed for solid state antenna switches used in commercial two-way radios.

Applications

- High Power Antenna Switch
(10W output two-way radio)

Dimensions



JEDEC DO-35

Absolute Maximum Ratings

Ta=25 °C

SYMBOL	PARAMETER	RATINGS	UNITS
VRM	Repetitive Peak Reverse Voltage	50	V
VR	Reverse Voltage	50	V
IFSM *	Forward Surge Current	2	A
P	Power Dissipation	500	mW
Tj	Junction Temperature	175	°C
Tstg	Storage Temperature	-55 to 175	°C

* t = 5sec


Electrical characteristics

Ta=25 °C


SYMBOL	PARAMETER	TEST CONDITIONS	LIMITS			UNITS
			MIN	TYP	MAX	
IR1	Reverse Current	VR = 50V			10	μ A
IR2		VR = 45V			0.5	μ A
IF	Forward Current	VF = 1.0V	100			mA
Ct	Diode Capacitance	VR = 0V, f = 100MHz		1.3	1.8	pF
r _{fs}	Forward Series Resistance	IF = 50mA, f = 470MHz		0.65	0.8	Ω
RP	Parallel Resistance	VR = 0V, f = 100MHz	1.0	6.0		k Ω

Electrical Characteristics


Forward Current vs. Forward Voltage




Reverse Current vs. Reverse Voltage




Forward Series Resistance vs. Forward Current



Diode Capacitance vs. Reverse Voltage



Parallel Resistance vs. Reverse Voltage



Ordering Information

WIDTH (mm)	TYPE	MINIMUM ORDER UNIT	ORDERING
26	Taping	2000 pcs./ Ammo Pack Box	XB15A****GT
52	Taping	2000 pcs./ Ammo Pack Box	XB15A****GT
52	Taping Reel	5000 pcs./ Reel	XB15A****GR
52	Bulk	100 pcs./ Bag x 10 Bags	XB15A****GB
12	Embossed tape	1500 pcs./ Reel	XB15A****HR

XB15 $\overline{O} \overline{OOO} \overline{O} \overline{O} \overline{O} \overline{O}$
 $\uparrow \quad \uparrow \quad \uparrow \quad \uparrow \quad \uparrow \quad \uparrow$
a b c d e f

SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION
a	Development order (A...)	c	Version
b	Series : 105 204 301 303 308 402 407 709	d	Lead length : 0 : No lead 1 : Short lead (26mm) 2 : Long lead (52mm)
		e	Package type : G : Glass shield H : Ceramic (no lead)
		f	Taping method : B : Bag T : Paper tape R : Embossed tape (no lead)

Note : With the 26mm width, only the XB15A105, XB15A204 and XB15A301 are available in the taping format.
Please further note that the XB15A105 has a 'Minimum Order Unit' of 5000 pcs./ Box and not 2000.

Taping Specification

Axial Taping

