


PA08M/883

SG	PARAMETER	SYMBOL	TEMP.	POWER	TEST CONDITIONS	MIN	MAX	UNITS
1	Quiescent Current	I_Q	25°C	±100V	$V_{IN} = 0, A_V = 100$		8.5	mA
1	Input Offset Voltage	V_{OS}	25°C	±100V	$V_{IN} = 0, A_V = 100$		2	mV
1	Input Offset Voltage	V_{OS}	25°C	±15V	$V_{IN} = 0, A_V = 100$		3.7	mV
1	Input Offset Voltage	V_{OS}	25°C	±150V	$V_{IN} = 0, A_V = 100$		3	mV
1	Input Bias Current, +IN	$+I_B$	25°C	±100V	$V_{IN} = 0$		50	pA
1	Input Bias Current, -IN	$-I_B$	25°C	±100V	$V_{IN} = 0$		50	pA
1	Input Offset Current	I_{OS}	25°C	±100V	$V_{IN} = 0$		50	pA
3	Quiescent Current	I_Q	-55°C	±100V	$V_{IN} = 0, A_V = 100$		9.5	mA
3	Input Offset Voltage	V_{OS}	-55°C	±100V	$V_{IN} = 0, A_V = 100$		4.4	mV
3	Input Offset Voltage	V_{OS}	-55°C	±15V	$V_{IN} = 0, A_V = 100$		6.1	mV
3	Input Offset Voltage	V_{OS}	-55°C	±150V	$V_{IN} = 0, A_V = 100$		5.4	mV
3	Input Bias Current, +IN	$+I_B$	-55°C	±100V	$V_{IN} = 0$		50	pA
3	Input Bias Current, -IN	$-I_B$	-55°C	±100V	$V_{IN} = 0$		50	pA
3	Input Offset Current	I_{OS}	-55°C	±100V	$V_{IN} = 0$		50	pA
2	Quiescent Current	I_Q	125°C	±100V	$V_{IN} = 0, A_V = 100$		12	mA
2	Input Offset Voltage	V_{OS}	125°C	±100V	$V_{IN} = 0, A_V = 100$		5	mV
2	Input Offset Voltage	V_{OS}	125°C	±15V	$V_{IN} = 0, A_V = 100$		6.7	mV
2	Input Offset Voltage	V_{OS}	125°C	±150V	$V_{IN} = 0, A_V = 100$		6	mV
2	Input Bias Current, +IN	$+I_B$	125°C	±100V	$V_{IN} = 0$		10	nA
2	Input Bias Current, -IN	$-I_B$	125°C	±100V	$V_{IN} = 0$		10	nA
2	Input Offset Current	I_{OS}	125°C	±100V	$V_{IN} = 0$		10	nA
4	Output Voltage, $I_o = 150mA$	V_o	25°C	±31V	$R_L = 100\Omega$	15		V
4	Output Voltage, $I_o = 29mA$	V_o	25°C	±150V	$R_L = 5K$	145		V
4	Output Voltage, $I_o = 80mA$	V_o	25°C	±90V	$R_L = 1K$	80		V
4	Current Limits	I_{CL}	25°C	±30V	$R_L = 100\Omega$	75	125	mA
4	Stability/Noise	E_N	25°C	±100V	$R_L = 5K, A_V = 1, C_L = 1nF$		1	mV
4	Slew Rate	SR	25°C	±100V	$R_L = 5K$	20	100	V/ μs
4	Open Loop Gain	A_{OL}	25°C	±100V	$R_L = 5K, F = 10Hz$		96	dB
4	Common Mode Rejection	CMR	25°C	±32.5V	$R_L = 5K, F = DC, V_{CM} = \pm 22.5V$		90	dB
6	Output Voltage, $I_o = 100mA$	V_o	-55°C	±31V	$R_L = 100\Omega$	10		V
6	Output Voltage, $I_o = 29mA$	V_o	-55°C	±150V	$R_L = 5K$	145		V
6	Output Voltage, $I_o = 70mA$	V_o	-55°C	±90V	$R_L = 1K$	70		V
6	Stability/Noise	E_N	-55°C	±100V	$R_L = 5K, A_V = 1, C_L = 1nF$		1	mV
6	Slew Rate	SR	-55°C	±100V	$R_L = 5K$	20	100	V/ μs
6	Open Loop Gain	A_{OL}	-55°C	±100V	$R_L = 5K, F = 10Hz$		96	dB
6	Common Mode Rejection	CMR	-55°C	±32.5V	$R_L = 5K, F = DC, V_{CM} = \pm 22.5V$		90	dB
5	Output Voltage, $I_o = 150mA$	V_o	125°C	±31V	$R_L = 100\Omega$	15		V
5	Output Voltage, $I_o = 29mA$	V_o	125°C	±150V	$R_L = 5K$	145		V
5	Output Voltage, $I_o = 80mA$	V_o	125°C	±90V	$R_L = 1K$	80		V
5	Stability/Noise	E_N	125°C	±100V	$R_L = 5K, A_V = 1, C_L = 1nF$		1	mV
5	Slew Rate	SR	125°C	±100V	$R_L = 5K$	20	100	V/ μs
5	Open Loop Gain	A_{OL}	125°C	±100V	$R_L = 5K, F = 10Hz$		96	dB
5	Common Mode Rejection	CMR	125°C	±32.5V	$R_L = 5K, F = DC, V_{CM} = \pm 22.5V$		90	dB

BURN IN CIRCUIT



- * These components are used to stabilize device due to poor high frequency characteristics of burn in board.
- ** Input signals are calculated to result in internal power dissipation of approximately 2.1W at case temperature = 125°C.