



JKL PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS)
BF22160-24B	LCD HIGH OUTPUT WHITE 8400°k RGB	800 @ 0°C	370	5 ± 1	38,000 ±10%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

METRIC			DIMENSIONS ARE IN MILLIMETERS		JKL COMPONENTS CORPORATION					
THIRD ANGLE PROJECTION			TOLERANCE UNLESS OTHERWISE SPECIFIED		TITLE					
			1 PL +/- 0.2		MINIATURE COLD CATHODE FLUORESCENT LAMP					
			2 PL +/- 0		DRAWING NO.					
			ANGLE +/- 0		BF22160-24B					
B DIM LINE CORRECT. AND 160+/-5.0 TO 160+/-3.0			3/14/00		SIZE		FSCM NO.		RELEASED DATE	
A LEAD LENGTH TO 17±3			3/14/00		A		55335		2/29/00	
RELEASED			2/29/00		SCALE		NONE		REVISION DATE	
REV. NO.			APPV'D DATE		- CAD DRAWING -		MANUAL REVISIONS NOT PERMITTED		REV. NO. B	
DESCRIPTION/ECO NUMBER									SHEET 1 OF 1	