



ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089
<http://www.nteinc.com>

NTE3133, NTE3135, NTE3136, NTE3138, NTE3139 Light Emitting Diode – 1.8mm

Features:

- All Plastic Mold Type w/Water Clear Lens:
 - NTE3133 (Super Yellow-Green, AlGaP/GaAs)
 - NTE3135 (Orange, AlInGaP/GaAs)
 - NTE3136 (Super Orange, AlInGaP/GaAs)
 - NTE3138 (Super Red, GaAlAs/GaAlAs)
 - NTE3139 (Super Blue, GaAlAs/GaAlAs)

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Power Dissipation, P_D	
NTE3133, NTE3135, NTE3136	100mW
NTE3138	110mW
NTE3139	120mW
Forward Current, I_F	
Continuous	25mA
Peak (Note 1)	
All Devices	50mA
NTE3139 Only	100mA
Reverse Voltage, V_R	
All Devices	5V
NTE3139 Only	4V
LED Junction Temperature, T_J	+100°C
Operating Temperature Range, T_{opr}	
All Devices	-30° to +85°C
NTE3139 Only	-25° to +85°C
Storage Temperature Range, T_{stg}	-40° to +100°C
Lead Temperature (During Soldering, 0.62 (1.6mm) from case, 3sec max), T_L	+240°C

Note 1. $t_p = 1\mu\text{sec}$ pulse, 0.3% duty cycle

Electrical Characteristics: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
View Angle of Half Power	2θ _{1/2}	$I_F = 20\text{mA}$	-	24	-	Degree
Forward Voltage	V_F	$I_F = 20\text{mA}$	-	2.20	2.40	V
NTE3133			-	2.00	2.60	V
NTE3135, NTE3136			-	1.86	2.50	V
NTE3138			-	3.5	4.0	V
NTE3139						

Electrical Characteristics (cont'd): ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Reverse Current	I_R	$V_R = 5V$	-	-	10	μA
NTE3139 Only			-	-	60	μA
Luminous Intensity	I_V	$I_F = 20\text{mA}$ (Note 2)	450	900	-	mcd
NTE3133			900	1300	-	mcd
NTE3135, NTE3136			700	1200	-	mcd
NTE3138			750	1500	-	mcd
Peak Emission Wavelength	λ_p	$I_F = 20\text{mA}$	-	575	-	nm
NTE3133			-	620	-	nm
NTE3135, NTE3136			-	660	-	nm
NTE3138			-	468	-	nm
Dominant Wavelength	$\lambda_{d(\text{HUE})}$	$I_F = 20\text{mA}$ (Note 3)	-	572	-	nm
NTE3133			-	615	-	nm
NTE3135, NTE3136			-	645	-	nm
NTE3138			470	472	475	nm
Spectrum Width of Half Valve	$\Delta\lambda$	$I_F = 20\text{mA}$	-	20	-	nm
NTE3139 Only			-	30	-	nm
Terminal Capacitance	C_t	$V = 0V, F = 1\text{MHz}$	-	35	-	pF
NTE3133			-	15	-	pF
NTE3135, NTE3136			-	22	-	pF
NTE3138						
Optic Rise Time (NTE3139 Only)	τ	$I_F = 20\text{mA}$	-	30	-	ns

Note 2. Tolerance: 30%, measured using Exeltron 2001.

Note 3. The dominant wavelength, λ_d , is derived from the CIE Chromaticity Diagram and represents the color of the device.

