
## 1N5400...1N5408 PLASTIC SILICON RECTIFIERS

## **FEATURES**

- \* Low forward voltage
- \* High current capability
- \* Low leakage current
- \* High surge capability
- \* Low cost



VOLTAGE RANCE 50 to 1000 Volts CURRENT 3.0 Amperes

Dimensions in mm

## **MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS**

Ratings at 25  $^{\circ}\text{C}$  ambient temperture unless otherwise specified. Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%

		1N5400	1N5401	1N5402	1N5403	1N5404	1N5405	1N5406	1N5407	1N5408	UNITS
* Maximum Recurrent Peak Reverse Voltage		50	100	200	300	400	500	600	800	1000	V
Maximum RMS Voltage		35	70	140	210	280	350	420	560	700	V
* Maximum DC Blocking Voltage to T <sub>A</sub> = 150 °C		50	100	200	300	400	500	600	800	1000	V
* Maximum Average Forward Rectified Current .5", (12.5mm) Lead Length at T <sub>A</sub> = 75 °C		3.0									Α
* Peak Forward Surge Current 8.3 ms single half sine-wave						150					Α
* Maximum Forward Voltage at 3.0A Peak		1.0									٧
* Maximum Reverse Current, at Rated DC Blocking Voltage	T <sub>A</sub> = 25 °C	10									μA
	$T_A = 150  ^{\circ}C$	500									μΑ
* Maximum Full Load Reverse Current, Full Cycle Average, .5", (12.5mm) Lead Lenght T <sub>A</sub> = 105 °C						500					μА
Typical Junction Capacitance (Note 1)			50								
* Storage Temperature Range T <sub>A</sub>			-65 to + 175								
* Operating Temperature Range T			-65 to + 170								

## NOTES:

- 1. Measured at 1.0 MHz and applied reverse voltage of 4.0 Volts
- \* JEDEC Registered Value.





