





6551-7212-AU 660nm 50 mW Laser Diodes AUTO PACKAGE

Specifications

Device Laser Diode
Package Type TO-18(5.6mm)



Top view



Absolute Maximum Ratings(Tc=25)

Characteristics	Symbols	Ratings	Units
Optical Output	Po	55	mW
Reverse Voltage	Laser	Vr	2 V
	PIN PD	Vr(PIN)	30 V
Operating Temperature	Top	-10 +40	
Storage Temperature	Tstg	-40 +85	

Electrical and optical Characteristics(Tc=25)

Characteristics	Symbols	Conditions	Min.	Typ.	Max.	Units	
Threshold Current	Ith	-	-	40	70	mA	
Operating Current	Iop	Po=50mW	-	120	150	mA	
Operating Voltage	Vop	Po=50mW	-	2.5	3	Volts	
Slope Efficiency		20mW	0.3	0.5	1.0	mW/mA	
		I(50mW)-I(30mW)					
Monitor Current	Im	Po=50mW	-	0.5	3.0	mA	
Beam Divergence (FWHM)	Parallel	//	Po=50mW	6	8.5	12	deg.
	Prependicular		Po=50mW	17	22	26	deg.
Parallel Deviation Angle	//	Po=50mW	-3	-	3	deg.	
Prependicular Deviation Angle		Po=50mW	-3	-	3	deg.	
Emission Point Accuracy	X	Po=50mW	-80	-	80	µm	
	Y	Po=50mW	-80	-	80	µm	
	Z	Po=50mW	-80	-	80	µm	
Lasng Wavelength		Po=50mW	655	660	665	nm	

Im is sorting by custom's need

// and are defined as the angle within which the intensity is 50% of the peak value.