



**AO4708**

## N-Channel Enhancement Mode Field Effect Transistor **SRFET™**





### General Description

**SRFET™** AO4708 uses advanced trench technology with a monolithically integrated Schottky diode to provide excellent  $R_{DS(ON)}$ , and low gate charge. This device is suitable for use as a low side FET in SMPS, load switching and general purpose applications. Standard Product AO4708 is Pb-free (meets ROHS & Sony 259 specifications). AO4708L is a Green Product ordering option. AO4708L and AO4708 are electrically identical.

### Features

$V_{DS}$  (V) = 30V  
 $I_D$  = 15A ( $V_{GS}$  = 10V)  
 $R_{DS(ON)} < 8.7\text{m}\Omega$  ( $V_{GS}$  = 10V)  
 $R_{DS(ON)} < 10.5\text{m}\Omega$  ( $V_{GS}$  = 4.5V)

**UIS TESTED!**  
*Rg, Ciss, Coss, Crss Tested*



**SRFET™**  
**Soft Recovery MOSFET:**  
 Integrated Schottky Diode

### Absolute Maximum Ratings $T_A=25^\circ\text{C}$ unless otherwise noted

Parameter	Symbol	Maximum	Units
Drain-Source Voltage	$V_{DS}$	30	V
Gate-Source Voltage	$V_{GS}$	$\pm 12$	V
Continuous Drain Current <sup>A</sup>	$T_A=25^\circ\text{C}$	15	A
$T_A=70^\circ\text{C}$	$I_{DSM}$	12	
Pulsed Drain Current <sup>B</sup>	$I_{DM}$	80	A
Avalanche Current <sup>B</sup>	$I_{AR}$	25	A
Repetitive avalanche energy $L=0.3\text{mH}$ <sup>B</sup>	$E_{AR}$	94	mJ
Power Dissipation <sup>A</sup>	$T_A=25^\circ\text{C}$	3.1	W
$T_A=70^\circ\text{C}$	$P_{DSM}$	2.0	
Junction and Storage Temperature Range	$T_J, T_{STG}$	-55 to 150	°C

### Thermal Characteristics

Parameter	Symbol	Typ	Max	Units
Maximum Junction-to-Ambient <sup>A</sup>	$t \leq 10\text{s}$	32	40	°C/W
Maximum Junction-to-Ambient <sup>A</sup>		60	75	°C/W
Maximum Junction-to-Lead <sup>C</sup>	$R_{\theta JL}$	17	24	°C/W

**Electrical Characteristics ( $T_J=25^\circ\text{C}$  unless otherwise noted)**

Symbol	Parameter	Conditions	Min	Typ	Max	Units
<b>STATIC PARAMETERS</b>						
$\text{BV}_{\text{DSS}}$	Drain-Source Breakdown Voltage	$I_D=250\mu\text{A}, V_{GS}=0\text{V}$	30			V
$I_{\text{DSS}}$	Zero Gate Voltage Drain Current	$V_{DS}=24\text{V}, V_{GS}=0\text{V}$ $T_J=125^\circ\text{C}$			0.1	mA
					20	
$I_{\text{GSS}}$	Gate-Body leakage current	$V_{DS}=0\text{V}, V_{GS}=\pm 12\text{V}$			0.1	$\mu\text{A}$
$V_{\text{GS(th)}}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu\text{A}$	1.4	1.8	2.4	V
$I_{\text{D(ON)}}$	On state drain current	$V_{GS}=4.5\text{V}, V_{DS}=5\text{V}$	80			A
$R_{\text{DS(ON)}}$	Static Drain-Source On-Resistance	$V_{GS}=10\text{V}, I_D=15\text{A}$ $T_J=125^\circ\text{C}$		7.2	8.7	$\text{m}\Omega$
				10.5	13.1	
$g_{\text{FS}}$	Forward Transconductance	$V_{DS}=5\text{V}, I_D=15\text{A}$		85		S
$V_{\text{SD}}$	Diode Forward Voltage	$I_S=1\text{A}, V_{GS}=0\text{V}$		0.39	0.5	V
$I_S$	Maximum Body-Diode + Schottky Continuous Current				5.5	A
<b>DYNAMIC PARAMETERS</b>						
$C_{\text{iss}}$	Input Capacitance	$V_{GS}=0\text{V}, V_{DS}=15\text{V}, f=1\text{MHz}$		2800	3360	pF
$C_{\text{oss}}$	Output Capacitance			390		pF
$C_{\text{rss}}$	Reverse Transfer Capacitance			145		pF
$R_g$	Gate resistance	$V_{GS}=0\text{V}, V_{DS}=0\text{V}, f=1\text{MHz}$		0.8	1.5	$\Omega$
<b>SWITCHING PARAMETERS</b>						
$Q_g(10\text{V})$	Total Gate Charge	$V_{GS}=10\text{V}, V_{DS}=15\text{V}, ID=15\text{A}$		42	52	nC
$Q_g(4.5\text{V})$	Total Gate Charge			19		nC
$Q_{\text{gs}}$	Gate Source Charge			7		nC
$Q_{\text{gd}}$	Gate Drain Charge			6		nC
$t_{\text{D(on)}}$	Turn-On DelayTime	$V_{GS}=10\text{V}, V_{DS}=15\text{V}, R_L=1\Omega, R_{\text{GEN}}=3\Omega$		7		ns
$t_r$	Turn-On Rise Time			7		ns
$t_{\text{D(off)}}$	Turn-Off DelayTime			31		ns
$t_f$	Turn-Off Fall Time			5		ns
$t_{\text{rr}}$	Body Diode Reverse Recovery Time	$I_F=15\text{A}, dI/dt=300\text{A}/\mu\text{s}$		13	15	ns
$Q_{\text{rr}}$	Body Diode Reverse Recovery Charge	$I_F=15\text{A}, dI/dt=300\text{A}/\mu\text{s}$		12		nC

A: The value of  $R_{\theta JA}$  is measured with the device in a still air environment with  $T_A=25^\circ\text{C}$ . The power dissipation  $P_{\text{DSM}}$  and current rating  $I_{\text{DSM}}$  are based on  $T_{J(\text{MAX})}=150^\circ\text{C}$ , using  $t \leqslant 10\text{s}$  junction-to-ambient thermal resistance.

B: Repetitive rating, pulse width limited by junction temperature  $T_{J(\text{MAX})}=150^\circ\text{C}$ .

C. The  $R_{\theta JA}$  is the sum of the thermal impedance from junction to lead  $R_{\theta JL}$  and lead to ambient.







D. The static characteristics in Figures 1 to 6 are obtained using  $<300\ \mu\text{s}$  pulses, duty cycle 0.5% max.

E. These tests are performed with the device mounted on 1 in 2 FR-4 board with 2oz. Copper, in a still air environment with  $T_A=25^\circ\text{C}$ . The SOA curve provides a single pulse rating.

Rev0: Sept. 2006

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.

## TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS



## TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note E)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note E)




Figure 11: Normalized Maximum Transient Thermal Impedance (Note E)

## TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS

