



TO-220 Plastic Package

CSC3039

CSC3039 NPN PLASTIC POWER TRANSISTOR
Switching Regulator Applications

PIN CONFIGURATION
 1. BASE
 2. COLLECTOR
 3. EMITTER
 4. COLLECTOR



DIM	MIN.	MAX.
A	14.42	16.51
B	9.63	10.67
C	3.56	4.83
D		0.90
E	1.15	1.40
F	3.75	3.88
G	2.29	2.79
H	2.54	3.43
J		0.56
K	12.70	14.73
L	2.80	4.07
M	2.03	2.92
N		31.24
O	DEG 7	

All dimensions in mm.

ABSOLUTE MAXIMUM RATINGS

Collector-base voltage (open emitter)
 Collector-emitter voltage (open base)
 Collector current
 Total power dissipation up to $T_C = 25^\circ C$
 Junction temperature
 Collector-emitter saturation voltage
 $I_C = 4A; I_B = 0.8A$
 D.C. current gain
 $I_C = 0.8 A; V_{CE} = 5 V$

V_{CB0}	max.	500 V
V_{CE0}	max.	400 V
I_C	max.	7.0 A
P_{tot}	max.	50 W
T_j	max.	150 °C
V_{CEsat}	max.	1.0 V
h_{FE}	min	15

RATINGS (at $T_A=25^\circ C$ unless otherwise specified)

Limiting values
 Collector-base voltage (open emitter)
 Collector-emitter voltage (open base)
 Emitter-base voltage (open collector)
 Collector current
 Collector current (Peak)
 Base current

V_{CB0}	max.	500 V
V_{CE0}	max.	400 V
V_{EBO}	max.	7.0 V
I_C	max.	7.0 A
I_{CP}	max.	14 A
I_B	max.	3 A

Total power dissipation up to $T_C = 25^\circ\text{C}$	P_{tot}	max.	50 W
Total power dissipation up to $T_A = 25^\circ\text{C}$	P_{tot}	max.	1.75 W
Junction temperature	T_j	max.	150 °C
Storage temperature	T_{stg}		-65 to +150 °C

CHARACTERISTICS

$T_{amb} = 25^\circ\text{C}$ unless otherwise specified

Collector cutoff current

$$I_E = 0; V_{CB} = 400\text{V}$$

$$I_{CBO} \quad \text{max.} \quad 10 \mu\text{A}$$

Emitter cut-off current

$$I_C = 0; V_{EB} = 5\text{V}$$

$$I_{EBO} \quad \text{max.} \quad 10 \mu\text{A}$$

Breakdown voltages

$$I_C = 5 \text{ mA}; I_B = 0$$

$$V_{CEO(sus)}^* \quad \text{min.} \quad 400 \text{ V}$$

$$I_C = 1 \text{ mA}; I_E = 0$$

$$V_{CBO} \quad \text{min.} \quad 500 \text{ V}$$

$$I_E = 1 \text{ mA}; I_C = 0$$

$$V_{EBO} \quad \text{min.} \quad 7.0 \text{ V}$$

Saturation voltages

$$I_C = 4 \text{ A}; I_B = 0.8 \text{ A}$$

$$V_{CEsat}^* \quad \text{max.} \quad 1.0 \text{ V}$$

$$V_{BEsat}^* \quad \text{max.} \quad 1.5 \text{ V}$$

D.C. current gain

$$I_C = 0.8\text{A}; V_{CE} = 5\text{V}$$

$$h_{FE}^* \quad \text{min.} \quad 15$$

$$I_C = 4\text{A}; V_{CE} = 5\text{V}$$

$$h_{FE}^* \quad \text{min.} \quad 8$$

Transition frequency

$$I_C = 0.8\text{A}; V_{CE} = 10\text{V}$$

$$f_T \quad \text{typ.} \quad 20 \text{ MHz}$$

Output capacitance $f = 1 \text{ MHz}$

$$I_E = 0; V_{CB} = 10\text{V}$$

$$C_o \quad \text{typ.} \quad 80 \text{ pF}$$

Switching time

$$I_C = 5\text{A}; I_{B1} = I_{B2} = -1\text{A}$$

$$R_L = 40\Omega; V_{CC} = 200\text{V}$$

Turn on time

$$t_{on} \quad \text{max.} \quad 1.0 \mu\text{s}$$

Storage time

$$t_{stg} \quad \text{max.} \quad 2.5 \mu\text{s}$$

Fall time

$$t_f \quad \text{max.} \quad 1.0 \mu\text{s}$$

* Pulse test: pulse width $\leq 300 \mu\text{s}$; duty cycle $\leq 2\%$.

(1) PW $\leq 300 \mu\text{s}$; duty cycle $\leq 10\%$.

Customer Notes

Disclaimer

The product information and the selection guides facilitate selection of the CDIL's Discrete Semiconductor Device(s) best suited for application in your product(s) as per your requirement. It is recommended that you completely review our Data Sheet(s) so as to confirm that the Device(s) meet functionality parameters for your application. The information furnished on the CDIL Web Site/ CD are believed to be accurate and reliable. CDIL however, does not assume responsibility for inaccuracies or incomplete information. Furthermore, CDIL does not assume liability whatsoever, arising out of the application or use of any CDIL product; neither does it convey any license under its patent rights nor rights of others. These products are not designed for use in life saving/support appliances or systems. CDIL customers selling these products (either as individual Discrete Semiconductor Devices or incorporated in their end products), in any life saving/support appliances or systems or applications do so at their own risk and CDIL will not be responsible for any damages resulting from such sale(s).

CDIL strives for continuous improvement and reserves the right to change the specifications of its products without prior notice.



CDIL is a registered Trademark of
Continental Device India Limited

C-120 Naraina Industrial Area, New Delhi 110 028, India.
Telephone + 91-11-2579 6150, 5141 1112 Fax + 91-11-2579 5290, 5141 1119
email@cdil.com www.cdilsemi.com