


PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
COM	COM	6E	6D	6C	DP5	5E	5D	5C	DP4	4E	4D	4C	DP3	3E	3D	3C
PIN	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32
COM	DP2	2E	2D	2C	DP1	1E	1D	1C	1B	1A	1F	1G	2B	2A	2F	2G
PIN	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48
COM	COL1	3B	3A	3F	3G	4B	4A	4F	4G	COL2	5B	5A	5F	5G	6B	6A
PIN	49	50														
COM	6F	6G														



- NOTES:
- 1.TOLERANCES UNLESS OTHERWISE SPECIFIED:  $\pm 0.20$
  - 2.VIEWING ANGLE: 12:00 O'CLOCK
  - 3.DISPLAY MODE: POSITIVE/TRANSFLECTIVE/TN TYPE
  - 4.DUTY CYCLE: STATIC
  - 5.DRIVING VOLTAGE: 5.0V
  - 6.OPERATING TEMP.:  $-20^{\circ}\text{C}$  TO  $80^{\circ}\text{C}$
  - 7.STORAGE TEMP.:  $-40^{\circ}\text{C}$  TO  $80^{\circ}\text{C}$

<b>AZ Displays, Inc.</b>	
DESIGN BY: D.X.W	SAMPLE: No <input type="checkbox"/> YES <input type="checkbox"/>
CHECKED BY:	CUSTOMER&TITLE:
APP BY:	GD-1873P UNIT: mm
DATE: AUG.1 2001	
SHEET 1 OF 1	
COMPOSE TYPE: MONO <input type="checkbox"/> ALONG <input type="checkbox"/>	
X-STEP: " # mm	
Y-STEP: " # mm	