

Round Type


φ 5.0 mm Pure Green LNG692CF6

Conventional Part No. Global Part No. Lighting Color
LNG692CF6 LNG692CF6 Pure Green

■ Absolute Maximum Ratings ($T_a = 25^\circ\text{C}$)

Lighting Color	$P_D(\text{mW})$	$I_F(\text{mA})$	$I_{FP}(\text{mA})^*$	$V_R(\text{V})$	$T_{opr}(^\circ\text{C})$	$T_{stg}(^\circ\text{C})$
Pure Green	120	30	100	5	$-25 \sim +80$	$-30 \sim +100$

★ I_{FP} の条件は, duty 10%, Pulse width 1 msec. The condition of I_{FP} is duty 10%, Pulse width 1 msec



■ Electro-Optical Characteristics ($T_a = 25^\circ\text{C}$)

Conventional Part No.	Lighting Color	Lens Color	I_O		I_F	V_F		λ_P	$\Delta\lambda$	I_F	I_R	
			Typ	Min		Typ	Max	Typ	Typ		Max	V_R
LNG692CF6	Pure Green	Clear	5000	3000	20	3.6	4.0	515	40	20	10	5
Unit	—	—	mcd	mcd	mA	V	V	nm	nm	mA	μA	V

