

Surface Mount

# Dual Matched MMIC Amplifiers


**NEW!**

**MERA-7433**

50Ω High Dynamic Range DC to 1 GHz

## Features

- Two matched amplifiers in one package
- InGaP HBT IF and RF amplifier
- frequency range, DC to 1 GHz, usable to 4 GHz
- high gain, 25 dB typ. at 100 MHz
- up to +19 dBm typ. output power at 100 MHz
- high IP3, +36 dBm at 100 MHz
- low noise figure, 2.7 dB typ.
- low thermal resistance
- transient protected
- patent pending
- useable as balanced and push pull amplifier



CASE STYLE: DL805  
PRICE: \$ 4.70 ea. QTY (25)

## Applications

- cellular
- catv
- VHF & UHF communication receivers & transmitters

## Electrical Specifications @ 25°C

Freq.* (GHz)	Gain, dB Typical A1, A2					Maximum Power (dBm)					Dynamic Range			VSWR (:1) Typ.		Maximum Rating**		DC Operating Power Pin 5, Pin 8		Thermal Resistance θjc, typ. °C/W	matching <sup>1</sup>									
																					Amplitude Unbalance between 2 amps (dB)		Phase Unbalance between 2 amps (deg.)							
	f <sub>L</sub> -f <sub>U</sub>	0.1	1	2	3	4	Min. @ 1GHz	0.1	1.0	2.0	Min. @ 0.1GHz	Input (no dmg.)	NF (dB) Typ.	0.1	0.5	1.0	In	Out	I (mA)	P (mW)	Current (mA)	Volt Typ	Min	Max	DC-1 GHz Typ.	1-4 GHz Typ. Max.	DC-1 GHz Typ.	1-4 GHz Typ.		
DC-1	25	22.4	19	16.2	13.4	20	19	18.3	14.8	18	10	2.7	36	35	32	1.25	1.8	130	700	80	4.8	4.3	5.3	120	0.15	0.3	0.3	—	0.5	1.0

\* Guaranteed specification DC-1GHz. Low frequency cutoff determined by external coupling capacitors.


\*\* Permanent damage may occur if any of these limits are exceeded.

These ratings are not intended for continuous normal operation. Reliability predictions and normal operating conditions are applicable at current specified.

## Pin Connections

PORT	
RF IN 1	1
RF OUT 1	8
RF IN 2	4
RF OUT 2	5
DC 1	8
DC 2	5
GROUND	2,3,6,7 and paddle

## MTTF vs. Junction Temp.




## Maximum Ratings<sup>2</sup>

Operating Case Temperature -45°C to 85°C


Storage Temperature -55°C to 100°C

2. See application note AN-60-032 for adequate heat sinking of paddle.


## typical biasing configuration



## Outline Drawing



## Demo Board MCL P/N: TB-294 Suggested PCB Layout (PL-165)



- NOTES:
1. TRACE WIDTH IS SHOWN FOR ROGERS R04350 WITH DIELECTRIC THICKNESS .020 ± .0015. COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.
  2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.

■ DENOTES PCB COPPER LAYOUT  
▨ DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

## Outline Dimensions (inch/mm)

A	B	C	D	E	F	G	H	J	K	L	M	N	P	Q	R	S	T	wt.
.128	.128	.035	.008	.080	.047	.013	—	.014	.026	.158	.158	.084	.013	.030	.048	.020	.025	grams
3.25	3.25	0.90	0.20	2.03	1.19	0.33	—	0.36	0.66	4.01	4.01	2.13	0.33	0.76	1.22	0.51	0.64	.02









Distribution Centers NORTH AMERICA 800-654-7949 • 417-335-5935 • Fax 417-335-5945 • EUROPE 44-1252-832600 • Fax 44-1252-837010






Mini-Circuits ISO 9001 & ISO 14001 Certified





INTERNET <http://www.minicircuits.com>

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

REV. OR  
M94145  
ED-11699/7  
WZ/TD/CP/AM  
041104







Freq. MHz	S11 (Input Return Loss)			S21 (Power Gain)			S12 (Isolation Out-in)			S22 (Output Return Loss)			K
	dB	Mag	ngle(deg)	dB	Mag	Angle	dB	Mag	Angle	dB	Mag	Angle	
20.00	-30.65	0.03	179.29	24.85	17.48	175.69	-27.79	0.04	-6.39	-19.19	0.11	177.75	1.05
30.00	-30.66	0.03	177.60	24.85	17.48	174.46	-27.51	0.04	-2.37	-19.01	0.11	177.20	1.04
50.00	-32.45	0.02	-161.44	24.83	17.44	171.30	-27.82	0.04	-5.22	-18.88	0.11	-178.75	1.05
100.00	-29.56	0.03	-151.50	24.76	17.30	163.47	-27.80	0.04	-7.16	-18.29	0.12	-174.46	1.05
200.00	-26.33	0.05	-154.32	24.54	16.87	148.12	-27.67	0.04	-15.11	-16.78	0.14	-174.26	1.05
300.00	-23.79	0.06	-158.15	24.32	16.44	132.94	-27.59	0.04	-23.26	-15.42	0.17	-178.51	1.05
400.00	-22.26	0.08	-168.49	24.08	16.00	118.16	-27.57	0.04	-29.47	-14.32	0.19	173.95	1.05
500.00	-21.39	0.09	-175.93	23.84	15.56	103.62	-27.56	0.04	-37.11	-13.28	0.22	164.41	1.05
600.00	-20.49	0.09	173.33	23.56	15.07	89.29	-27.31	0.04	-45.16	-12.40	0.24	154.36	1.04
700.00	-19.65	0.10	164.46	23.28	14.59	75.03	-27.23	0.04	-53.21	-11.60	0.26	144.53	1.03
800.00	-19.09	0.11	155.72	22.98	14.09	61.16	-27.12	0.04	-60.84	-10.99	0.28	134.01	1.03
900.00	-18.46	0.12	146.31	22.65	13.57	47.37	-27.06	0.04	-68.96	-10.47	0.30	123.23	1.03
1000.00	-18.03	0.13	135.98	22.34	13.09	33.83	-26.88	0.05	-76.45	-9.99	0.32	112.52	1.03
1100.00	-17.45	0.13	126.04	22.01	12.60	20.31	-26.76	0.05	-85.37	-9.59	0.33	101.33	1.03
1200.00	-17.02	0.14	115.92	21.69	12.15	7.13	-26.62	0.05	-93.13	-9.25	0.34	90.22	1.03
1400.00	-16.43	0.15	96.35	21.03	11.26	-18.81	-26.34	0.05	-110.21	-8.69	0.37	68.01	1.03
1600.00	-15.90	0.16	75.14	20.36	10.42	-44.16	-25.98	0.05	-126.57	-8.23	0.39	45.75	1.03
1800.00	-15.40	0.17	55.21	19.74	9.71	-69.29	-25.67	0.05	-144.16	-7.85	0.41	23.63	1.03
2000.00	-15.10	0.18	32.91	19.10	9.02	-93.79	-25.30	0.05	-161.62	-7.58	0.42	1.42	1.04
2200.00	-14.76	0.18	10.19	18.48	8.39	-118.18	-24.95	0.06	-179.21	-7.38	0.43	-20.95	1.05
2400.00	-14.53	0.19	-13.49	17.86	7.82	-142.32	-24.63	0.06	162.18	-7.19	0.44	-43.18	1.06
2600.00	-14.24	0.19	-37.58	17.29	7.32	-166.14	-24.31	0.06	143.76	-6.97	0.45	-65.80	1.07
2800.00	-13.80	0.20	-62.42	16.70	6.84	169.92	-24.05	0.06	124.96	-6.76	0.46	-88.26	1.09
3000.00	-13.38	0.21	-88.07	16.14	6.41	146.11	-23.76	0.06	106.00	-6.59	0.47	-110.89	1.11
3200.00	-12.96	0.22	-114.09	15.55	5.99	122.70	-23.55	0.07	86.92	-6.44	0.48	-133.80	1.13
3400.00	-12.44	0.24	-140.05	14.97	5.60	99.38	-23.27	0.07	67.26	-6.30	0.48	-156.85	1.16
3600.00	-11.81	0.26	-165.14	14.42	5.26	76.07	-23.08	0.07	48.16	-6.08	0.50	-179.84	1.18
3800.00	-10.88	0.29	169.74	13.87	4.94	52.67	-22.93	0.07	27.88	-5.83	0.51	157.00	1.20
4000.00	-10.07	0.31	145.06	13.31	4.63	29.38	-22.83	0.07	8.09	-5.58	0.53	134.24	1.22
4500.00	-8.28	0.39	86.65	11.77	3.88	-28.13	-22.67	0.07	-41.31	-4.91	0.57	77.08	1.28
5000.00	-6.72	0.46	31.04	10.10	3.20	-84.70	-22.71	0.07	-90.46	-4.33	0.61	22.74	1.36
5500.00	-5.56	0.53	-21.51	8.45	2.65	-139.53	-22.90	0.07	-138.68	-3.80	0.65	-29.26	1.44
6000.00	-4.76	0.58	-71.40	6.81	2.19	166.96	-23.05	0.07	174.30	-3.54	0.67	-79.39	1.54
6500.00	-4.19	0.62	-119.47	5.17	1.81	114.74	-23.32	0.07	126.45	-3.33	0.68	-128.40	1.67
7000.00	-3.76	0.65	-166.39	3.60	1.51	63.79	-23.31	0.07	82.26	-3.21	0.69	-175.94	1.79
7500.00	-3.54	0.67	148.39	2.25	1.30	14.43	-23.39	0.07	37.02	-3.07	0.70	137.82	1.92
8000.00	-3.35	0.68	103.42	1.12	1.14	-34.61	-23.31	0.07	-8.50	-2.99	0.71	92.53	2.01
9000.00	-3.27	0.69	11.87	-0.47	0.95	-133.18	-22.84	0.07	-101.64	-2.87	0.72	1.30	2.09
10000.00	-3.35	0.68	-87.43	-1.86	0.81	125.16	-22.49	0.08	159.53	-2.74	0.73	-92.89	2.23
11000.00	-3.33	0.68	167.73	-3.12	0.70	19.23	-22.80	0.07	56.32	-2.85	0.72	171.76	2.62