



60×40×22

# NE720



CH0054066—2000

## Features

- Magnet latching relay.
- High sensitivity & reliability.
- Well anti-shock and anti-vibration.
- Heavy contact load.

## Ordering Information

**NE720 A Z DC12V**

1 2 3 4

1 Part number: NE720

2 Contact arrangement: A:1A; B:1B

3 Enclosure: Z: Dust cover

4 Coil rated Voltage(V): DC:6,12, 24

## Contact Data

|                                    |                          |                                       |
|------------------------------------|--------------------------|---------------------------------------|
| Contact Arrangement                | 1A (SPSTNO), 1B (SPSTNC) |                                       |
| Contact Material                   | Ag-SnO <sub>2</sub>      |                                       |
| Contact Rating(resistive)          | 100Amax/240VAC           |                                       |
| Max. Switching Power               | 23000VA(COSΦ=1)          | 2300VA(COSΦ=0.4)                      |
| Max. Switching Voltage             | 400VAC                   | Max. Switching Current:100A           |
| Contact Resistance or Voltage drop | ≤1mΩ                     | Item 3.12 of IEC255-7                 |
| Operation life                     | Electrical (Rated load)  | 10 <sup>4</sup> Item 3.30 of IEC255-7 |
|                                    | Mechanical (No load)     | 10 <sup>6</sup> Item 3.31 of IEC255-7 |

## Coil Parameter

| DASH NUMBERS | COIL RATED VOLTAGE VDC | COIL RESISTANCE Ω±10% | SWITCHING VOLTAGE VDC (<80% of rated voltage) | OPERATING VOLTAGE RANGE VDC | PULSE MAGNITUDE ms | COIL POWER CONSUMPTION W | Operate Time ms | Reset Time ms |
|--------------|------------------------|-----------------------|---|-----------------------------|--------------------|--------------------------|-----------------|---------------|
| 2 COIL       |                        |                       |   |                             |                    |                          |                 |               |
| 006-4500     | 6                      | 2×8                   | <4.8  | 4.9~10                      | ≥36                | 4.5                      | <12             | <6            |
| 012-4500     | 12                     | 2×32                  | <9.6  | 9.8~20                      |                    |                          |                 |               |
| 024-4500     | 24                     | 2×130                 | <19.2   | 19.7~40                     |                    |                          |                 |               |
| 1 COIL       |                        |                       |   |                             |                    |                          |                 |               |
| 006-2250     | 6                      | 16                    | <4.8  | 4.9~10                      | ≥36                | 2.25                     | <12             | <6            |
| 012-2250     | 12                     | 64                    | <9.6  | 9.8~20                      |                    |                          |                 |               |
| 024-2250     | 24                     | 260                   | <19.2   | 19.7~40                     |                    |                          |                 |               |

**CAUTION:** 1.When latching relays are installed in equipment, the latch and reset coil should not be pulsed simultaneously. coil should not be pulsed with less than the nominal coil voltage and pulse width should be a minimum of three times the specified operate time of the relay. If these conditions are not followed, it is possible for the relay to in be the magnetically neutral position .  
2.Switching voltage is for test purpose only and are no to be used as design criteria.

**Operation condition**

|                          |   |                             |
|--------------------------|---|-----------------------------|
| Insulation Resistance    | 1000MΩ min (at 500VDC)  | Item 7 of IEC255-5          |
| Dielectric Strength      |   |                             |
| Between contacts         | 50Hz 2000V surge Voltage 2kV  | Item 6 and 8 of IEC255-5    |
| Between contact and coil | 50Hz 4000V surge Voltage 12kV   | Item 6 and 8 of IEC255-5    |
| Creepage distance        | 8.4mm   | Addenda B of IEC255-5       |
| Shock resistance         | Functional 100m/s <sup>2</sup> ; Survival: 1000 m/s <sup>2</sup> 11ms | IEC68-2-27 Test Ea          |
| Vibration resistance     | 10~55Hz Double amplitude 1.5mm  | IEC68-2-6 Test Fc           |
| Terminals strength       | 5N; 2.5N · m  | IEC68-2-21 Test Ua1 and Ud  |
| Solderability            | 235°C ± 2°C 3 ± 0.5s  | IEC68-2-20 Test Ta method 1 |
| Ambient Temperature      | -25~70°C  |                             |
| Relative Humidity        | 85% (at 40°C)   |                             |
| Mass                     | 82g   | IEC68-2-3 Test Ca           |

**Qualification inspection:**

Perform the qualification test as specified in the table IV of IEC255-19-1 and minimum sample size 24.

**Safety approvals**

|                 |             |
|-----------------|-------------|
| Safety approval | CCEE        |
| Load            | 100A/250VAC |

**Dimensions (Unit: mm)**

|  | mm    | inch  |
|--|-------|-------|
|  | 0.4   | 0.016 |
|  | 0.6   | 0.024 |
|  | 0.7   | 0.027 |
|  | 5.0   | 0.197 |
|  | 6.0   | 0.236 |
|  | 6.16  | 0.243 |
|  | 11.0  | 0.433 |
|  | 12.0  | 0.472 |
|  | 13.0  | 0.512 |
|  | 14.5  | 0.571 |
|  | 15.0  | 0.597 |
|  | 19.2  | 0.756 |
|  | 22.0  | 0.866 |
|  | 36.1  | 1.441 |
|  | 40.0  | 1.575 |
|  | 44.35 | 1.746 |
|  | 45.0  | 1.772 |
|  | 47.5  | 1.870 |
|  | 60.0  | 2.362 |

**Dimensions**

**Wiring diagram**

**Mounting (Bottom views)**

**NOTES**

- 1). Dimensions are in millimeter.
- 2). Inch equivalents are given for general information only.
- 3). Relays shall have plus(+) or plus(+) and minus(-) signs placed on the circuit diagram as shown.