

JRC SAW FILTER

NSVA288

Application

PAGER 930MHz

Electrical Specification: (Table 1)

The device characteristics are measured in the circuit shown in Fig.1.

Table 1. Electrical Specifications

Item		Spec.
Input and Output Impedance		50Ω
Nominal Center Frequency (f0)		930MHz
Insertion Loss	928~932MHz	3.5dB max.
Response Variation	928~932MHz	1.2dB max.
Out of Band Rejection (Relative to Through Level)	630~910.7MHz	40dB min.
	961.8~965.1MHz	27dB min.
	990~1030MHz	40dB min.

(Operating Temperature Range: -10~+60°C)

Maximum Rating: (Table 2)

Table 2. Maximum Ratings

Item	Rating
Maximum Input Power	0dBm
Maximum DC Voltage	7.5V
Operating Temperature Range	-10~+60°C
Storage Temperature	-30~+85°C

Mechanical Specifications: (Fig.2)

Package is designed as small as 3.5x3.5x1.0[mm³] for SMD (Surface Mount Device) type.

Notice:

This part is electrostatic discharge sensitive and may be damaged by improper handling.

Communications Equipment Division
Communications Equipment Marketing Department

Japan Radio Co., Ltd.

17-22 Akasaka 2-chome minato-ku,

Tokyo. 107-0052 Japan

Tel. +81 3-3584-8811

Fax. +81 3-3584-8876

http://www.jrc.co.jp/product/comm/device/saw/saw_top.html (Japanese)

http://www.jrc.co.jp/product/comm/device/saw/saw_top_e.html (English)





Fig.1 Measuring circuit



Marking

(1) Manufacturer's Mark

(2) Lot Number

(a) Year

(b) Month

*Oct.--- X

Nov.--- Y

Dec.--- Z

(3) Part number Mark




Fig.2 Package dimensions (in mm)

Pin no.	Connection
1	GND
2	IN/OUT
3	GND
4	GND
5	GND
6	OUT/IN
7	GND
8	GND




Fig.3 Desirable land area (in mm)

Notice


1. Use this component within operating temperature range. It might not be satisfied with electrical specification without operating temperature range. When it is used less than -10°C or more than $+60^{\circ}\text{C}$, it might be a cause of degradation or destruction of the component. Even if it endures during a short time, it causes degradation of qualification.
2. When soldering iron is used, solder with the temperature at the tip of soldering iron: 350°C max., the time of soldering: 10 seconds max., the power of soldering iron: 30W max..
3. Notice that the allowed time of soldering with soldering iron is accumulated time, when soldering is repeated.
4. As rapid temperature change for cleaning after reflow soldering might be a cause of destruction clean this component after confirming that temperature of this component goes down to room temperature.
5. Confirm that there are not any influence for qualification to this component in mounting on PCB when this component is cleaned.
6. As it might be a cause of degradation or destruction to apply static electricity to this component, do not apply static electricity or excessive voltage while assembling and measuring. And do not transport this component with bare hand.
7. As it might be a cause of degradation or destruction to apply D.C. voltage between each terminal, apply D.C. voltage 7.5V max. in actual circuit.

Note

1. This specification specifies the quality of this component as a single unit. Make sure that this component is evaluated and confirmed against this specification when it is mounted to your products.

7 Jan 1997 18:39:39

CH1 MEM log MAG 1 dB/ REF 0 dB 1 -1.6903 dB
CH2 MEM log MAG 10 dB/ REF 0 dB 1: -1.6932 dB




CENTER 930.000 000 MHz SPAN 200.000 000 MHz

7 Jan 1987 18:58:11
 CH1 S11 1 U FB 1: 40.314 a 2.823 a 449.88 pH
 928.000 000 MHz

PRM
 Cor

H1d




CENTER 930.000 000 MHz SPAN 100.000 000 MHz

7 Jan 1987 18:58:07
 CH1 S11 SWR 1 / REF 1 1: 1.2498
 928.000 000 MHz

PRM
 Cor

H1d




CENTER 930.000 000 MHz SPAN 100.000 000 MHz

7 Jan 1987 18:04:27
 CH1 S22 1 U FB 1: 37.784 a 3.752 a 843.47 pH
 928.000 000 MHz

PRM
 Cor

H1d




CENTER 930.000 000 MHz SPAN 100.000 000 MHz

7 Jan 1987 18:04:17
 CH1 S22 SWR 1 / REF 1 1: 1.3428
 928.000 000 MHz

PRM
 Cor

H1d



CENTER 930.000 000 MHz SPAN 100.000 000 MHz

7 Jan 1997 19:26:38

CH2 MEM 10g MAG 10 dB/ REF 0 dB

