

**Micro Commercial Components** 

Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933

(818) 701-4939 Fax:

**RS3000** 

## 200 Milliamp **High Voltage** Silicon Rectifier **3000 Volts**

### **Features**

- Low Cost
- Low Leakage
- Low Forward Voltage Drop
- **High Current Capability**
- High Voltage
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0


# **Maximum Ratings**

- Operating Temperature: -55°C to +150°C
- Storage Temperature: -55°C to +150°C

r					
ı	MCC	Device	Maximum	Maximum	Maximum
	Part	Marking	Recurrent	RMS	DC
ı	Number		Peak Reverse	Voltage	Blocking
l			Voltage		Voltage
ĺ	RS3000	RS3000	3000V	2100V	3000V

### Electrical Characteristics @ 25°C Unless Otherwise Specified

Average Forward Current	I <sub>F(AV)</sub>	200mA	T <sub>A</sub> = 50°C
Peak Forward Surge Current	I <sub>FSM</sub>	30A	8.3ms, half sine
Maximum Instantaneous Forward Voltage			
J	$V_{F}$	4.0V	I <sub>FM</sub> = 0.5A; T <sub>A</sub> = 50°C
Maximum DC Reverse Current At Rated DC Blocking Voltage	I <sub>R</sub>	5.0μA 50μA	T <sub>A</sub> = 25°C T <sub>A</sub> = 100°C
Typical Junction Capacitance	CJ	30pF	Measured at 1.0MHz, V <sub>R</sub> =4.0V




DIMENSIONS										
	INCHES		MM							
DIM	MIN	MAX	MIN	MAX	NOTE					
Α	.166	.205	4.10	5.20						
В	.080	.107	2.00	2.70						
С	.028	.034	.70	.90						
О	1.000		25.40							




#### **Micro Commercial Components**

Figure 1 Typical Reverse Characteristics 2 1 .8 .6 .4 .2 μΑ .1 .08 .06 .04 T<sub>J</sub> = 25 C .02 .01 40 60 80 100 120 20

Volts
Instantaneous Reverse Current - Micro Ampsversus
Percent Of Rated Peak Reverse Voltage - Volts



Average Forward Rectified Current - Amperes/ersus Ambient Temperature -°C



Peak Forward Surge Current - Amperesversus Number Of Cycles At 60Hz - Cycles



#### **Micro Commercial Components**

#### \*\*\*IMPORTANT NOTICE\*\*\*

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes.
Micro Commercial Components Corp. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Micro Commercial Components Corp. and all the companies whose products are represented on our website, harmless against all damages.

#### \*\*\*APPLICATIONS DISCLAIMER\*\*\*

Products offer by *Micro Commercial Components Corp* . are not intended for use in Medical,

Aerospace or Military Applications.