



# SP1020 THRU SP10100 10 A Schottky Barrier Rectifiers

Voltage Range 20 to 100 Volts  
Current 10.0 Amperes


## Features

- \* Low forward voltage drop
- \* High current capability
- \* High reliability
- \* High surge current capability
- \* Epitaxial construction

## Mechanical Data

- \* Case: Molded plastic
- \* Epoxy: UL 94V-0 rate flame retardant
- \* Lead: Axial leads, solderable per MIL-STD-202, method 208 guaranteed
- \* Polarity: Color band denotes cathode end
- \* Mounting position: Any
- \* Weight: 2.24 grams

ITO-220



Dimensions in inches and (millimeters)

## Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate current by 20%

Type Number	SP1020	SP1030	SP1040	SP1050	SP1060	SP1080	SP10100	Units
Maximum Recurrent Peak Reverse Voltage	20	30	40	50	60	80	100	v
Maximum RMS Voltage	14	21	28	35	42	56	70	v
Maximum DC Blocking Voltage	20	30	40	50	60	80	100	v
Maximum Average Forward Rectified Current See Fig. 1	10							A
Peak Forward Surge Current, 8.3 ms Single Half Sinewave - Superimposed on Rated Load method (JEDEC)	130				100			A
Maximum Instantaneous Forward Voltage @ 5.0A	0.65		0.75		0.85			V
Maximum D.C. Reverse Current @ T <sub>A</sub> =25°C	1							mA
At Rated DC Blocking Voltage @ T <sub>A</sub> =100°C	100							mA
Typical Junction Capacitance (Note 1)	700		460		280			pF
Typical Thermal Resistance R <sub>JA</sub> (Note 2)	3.5							°C/W
Operating Junction Temperature Range T <sub>J</sub>	-50+125							°C
Storage Temperature Range T <sub>STG</sub>	-65+150							°C

Notes:

1. Measured at 1MHz and applied reverse voltage of 4.0Volts D.C.
2. Thermal Resistance Junction to Case



# SP1020 THRU SP10100

## 10 A Schottky Barrier Rectifiers

Voltage Range 20 to 100 Volts  
Current 10.0 Amperes

### RATING AND CHARACTERISTIC CURVES (SP1020 THRU SP10100)

FIG.1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2-TYPICAL FORWARD CHARACTERISTICS




FIG.3-MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG.5 - TYPICAL REVERSE CHARACTERISTICS




FIG.4-TYPICAL JUNCTION CAPACITANCE

