



**Solid State Devices, Inc.**

14701 Firestone Blvd \* La Mirada, Ca 90638  
 Phone: (562) 404-4474 \* Fax: (562) 404-1773  
 ssdi@ssdi-power.com \* www.ssdi-power.com

**SPD5802 thru SPD5806  
 and  
 SPD5802SMS thru SPD5806SMS**

**Designer's Data Sheet**

**Part Number/Ordering Information <sup>1/</sup>**

**SPD**                        

**Screening <sup>2/</sup>**

- = Not Screened
- TX = TX Level
- TXV = TXV
- S = S Level

**Package Type**

- = Axial Leaded
- SMS = Surface Mount Square Tab

**Voltage/Family**

- 5802 = 50V
- 5804 = 100V
- 5806 = 150V

**LOW LEAKAGE  
 2.0 AMPS  
 50 – 150 VOLTS  
 25 ns HYPERFAST RECOVERY  
 RECTIFIER**

**FEATURES:**

- Hyper Fast Reverse Recovery: 25ns Maximum <sup>4/</sup>
- PIV to 150 Volts (Voltages Up To 300V Available)
- Hermetically Sealed
- Low Forward Voltage Drop
- Void Free Chip Construction
- For High Efficiency Applications
- Available in Axial & Square Tab Versions
- TX, TXV, and S-Level Screening Available <sup>2/</sup>
- Low Leakage Replacement for: 1N 5802, US thru 1N5806, US


**MAXIMUM RATINGS <sup>3/</sup>**

RATING		SYMBOL	VALUE	UNIT
Peak Repetitive Reverse Voltage And DC Blocking Voltage	SPD5802	$V_{RRM}$	50	Volts
	SPD5804	$V_{RWM}$	100	
	SPD5806	$V_R$	150	
Average Rectified Forward Current	(Resistive Load, 60Hz, Sine Wave, $T_A = 25^\circ C$ )	$I_O$	2.0	Amps
Peak Surge Current (8.3ms pulse, half sine wave superimposed on $I_O$ , allow junction to reach equilibrium between pulses, $T_A = 25^\circ C$ )		$I_{FSM}$	50	Amps
Operating & Storage Temperature		$T_J$ and $T_{STG}$	-65 to +175	$^\circ C$
Thermal Resistance	Junction to Lead for Axial, L = .375"	$R_{\theta JL}$	38	$^\circ C/W$
	Junction to End Tab for Surface Mount	$R_{\theta JE}$	25	


**NOTES:**

- 1/** For Ordering Information, Price, Operating Curves, and Availability- Contact Factory.
- 2/** Screened to MIL-PRF-19500.
- 3/** Unless Otherwise Specified, All Electrical Characteristics @25°C.
- 4/**  $I_F = 500mA$ ,  $I_R = 1A$ ,  $I_{RR} = 250mA$ ,  $T_A = 25^\circ C$

**Axial Leaded**



**SMS**



**NOTE:** All specifications are subject to change without notification. SCD's for these devices should be reviewed by SSDI prior to release.

**DATA SHEET #: RC0107A**

**DOC**



**Solid State Devices, Inc.**

14701 Firestone Blvd \* La Mirada, Ca 90638  
 Phone: (562) 404-4474 \* Fax: (562) 404-1773  
 ssdi@ssdi-power.com \* www.ssdi-power.com

**SPD5802 thru SPD5806  
 and  
 SPD5802SMS thru SPD5806SMS**

**ELECTRICAL CHARACTERISTICS <sup>3/</sup>**

CHARACTERISTICS	SYMBOL	VALUE	UNIT
		<b>MAX</b>	
Instantaneous Forward Voltage Drop $I_F = 2.0 \text{ Adc}, T_A = +25^\circ\text{C}, 300 - 500\mu\text{s pulse}$ $I_F = 2.0 \text{ Adc}, T_A = -55^\circ\text{C}, 300 - 500\mu\text{s pulse}$	$V_{F1}$ $V_{F2}$	.975 1.1	Vdc
Reverse Leakage Current (Rated $V_R, T_A = +25^\circ\text{C}$ ) (Rated $V_R, T_A = +100^\circ\text{C}$ )	$I_{R1}$ $I_{R2}$	1 100	$\mu\text{A}$
Junction Capacitance $V_R = 10 \text{ Vdc}, f = 1\text{MHz}, T_A = 25^\circ\text{C}$	$C_J$	45	pF
Maximum Reverse Recovery Time $I_F = 500\text{mA}, I_R = 1\text{A}, I_{RR} = 250\text{mA}, T_A = 25^\circ\text{C}$	$t_{rr}$	25	ns

**NOTES:**

- 1/ For Ordering Information, Price, Operating Curves, and Availability- Contact Factory.
- 2/ Screened to MIL-PRF-19500.
- 3/ Unless Otherwise Specified, All Electrical Characteristics @25°C.
- 4/  $I_F = 500\text{mA}, I_R = 1\text{A}, I_{RR} = 250\text{mA}, T_A = 25^\circ\text{C}$

**Package Outlines:**

DIMENSIONS (inches)			DIMENSIONS (inches)		
DIM.	Minimum	Maximum	DIM.	Minimum	Maximum
A	---	.140	A	.134	.155
B	.190	.230	B	.230	.280
C	.027	.033	C	.022	.028
D	1.00	---	D	.002	---

**AXIAL**

**SMS**