



# SR802 THRU SR810

## 8.0 AMPS. Schottky Barrier Rectifiers

	<b>Voltage Range</b> 20 to 100 Volts <b>Current</b> 8.0 Amperes
--	--

<p><b>Features</b></p> <ul style="list-style-type: none"> <li>✧ Low forward voltage drop</li> <li>✧ High current capability</li> <li>✧ High reliability</li> <li>✧ High surge current capability</li> </ul> <p><b>Mechanical Data</b></p> <ul style="list-style-type: none"> <li>✧ Cases: DO-201AD molded plastic</li> <li>✧ Epoxy: UL 94V-O rate flame retardant</li> <li>✧ Lead: Axial leads, solderable per MIL-STD-202, Method 208 guaranteed</li> <li>✧ Polarity: Color band denotes cathode end</li> <li>✧ High temperature soldering guaranteed: 260°C/10 seconds/.375", (9.5mm) lead lengths at 5 lbs., (2.3kg) tension</li> <li>✧ Weight: 1.1 grams</li> </ul>	<p><b>DO-201AD</b></p> <p style="text-align: center;"><b>Dimensions in inches and (millimeters)</b></p>
---	---

**Maximum Ratings and Electrical Characteristics**  
 Rating at 25°C ambient temperature unless otherwise specified.  
 Single phase, half wave, 60 Hz, resistive or inductive load.  
 For capacitive load, derate current by 20%

Type Number	Symbol	SR 802	SR 803	SR 804	SR 805	SR 806	SR 809	SR 810	Units
Maximum Recurrent Peak Reverse Voltage	$V_{RRM}$	20	30	40	50	60	90	100	V
Maximum RMS Voltage	$V_{RMS}$	14	21	28	35	42	63	70	V
Maximum DC Blocking Voltage	$V_{DC}$	20	30	40	50	60	90	100	V
Maximum Average Forward Rectified Current See Fig. 1	$I_{(AV)}$	8.0							A
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method )	$I_{FSM}$	175					150		A
Maximum Instantaneous Forward Voltage @8.0A	$V_F$	0.55			0.70		0.92		V
Maximum D.C. Reverse Current @ $T_A=25^\circ\text{C}$ at Rated DC Blocking Voltage @ $T_A=100^\circ\text{C}$	$I_R$	0.5 50					0.1 -		mA mA
Typical Thermal Resistance (Note 1)	$R_{\theta JA}$	40							°C/W
Typical Junction Capacitance (Note 2)	$C_j$	500			270		165		pF
Operating Junction Temperature Range	$T_J$	-65 to +125			-65 to +150				°C
Storage Temperature Range	$T_{STG}$	-65 to +150							°C

Notes: 1. Mount on Cu-Pad Size 16mm x 16mm on P.C.B.  
 2. Measured at 1 MHz and Applied Reverse Voltage of 4.0V D.C.

## RATINGS AND CHARACTERISTIC CURVES (SR802 THRU SR810)

FIG.1- MAXIMUM FORWARD CURRENT DERATING CURVE




FIG.2- TYPICAL FORWARD CHARACTERISTICS




FIG.3- MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG.5- TYPICAL REVERSE CHARACTERISTICS




FIG.4- TYPICAL JUNCTION CAPACITANCE PER LEG

