


Part Number: SL22 50004

### Ordering Different Lead Types:

Inside Kinked Leads	Use <b>-A</b> after Ametherm's part #
Outside Kinked Leads	Use <b>-B</b> after Ametherm's part #

For example: to order an inside kinked lead use part number SL22 50004-A



### Electrical Specifications:

Resistance @ 25°C	50.0 $\Omega$ $\pm$ 20%
Max Steady State Current Up to 65°C	4.0 A
Max Recommended Voltage	265 VAC
Max Recommended Energy Rating (Joules)	80.0 J
Actual Failure Point of Instantaneous Energy (Joules)	175.0 J
Resistance @ 100% of Max Current	0.440 $\Omega$
Resistance @ 50% of Max Current	0.900 $\Omega$
Body Temperature @ 100% Current Rating	162 °C
Dissipation Constant	32.4mW/°C
Thermal Time Constant	94 seconds
Material Type	"M"
Upper Limit of the Body Temperature	270 °C
Max Recommended Capacitance @ 120VAC/240 VAC	5500 $\mu$ /1300 $\mu$ F

### Mechanical Specifications:

D	20.0 $\pm$ 1.0 mm
T	5.0 $\pm$ 0.2 mm
Lead Diameter	1.0 $\pm$ 0.1 mm
S	7.8 $\pm$ 2.0 mm
L	38.0 $\pm$ 9.0 mm
Straight Leads Coating Run Down	5.0 $\pm$ 1.0 mm
B	9.22 $\pm$ 1.0 mm
C	3.82 $\pm$ 1.0 mm