

SUPER FAST RECTIFIER

VOLTAGE RANGE: 50 --- 200 V

CURRENT: 2.0 A


FEATURES

- ◇ Low cost
- ◇ Low leakage
- ◇ Low forward voltage drop
- ◇ High current capability
- ◇ Easily cleaned with alcohol, Isopropanol and similar solvents
- ◇ The plastic material carries U/L recognition 94V-0

MECHANICAL DATA

- ◇ Case: JEDEC DO-15, molded plastic
- ◇ Terminals: Axial lead, solderable per MIL-STD-202, Method 208
- ◇ Polarity: Color band denotes cathode
- ◇ Weight: 0.014 ounces, 0.39 grams
- ◇ Mounting position: Any

DO - 15



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate by 20%.

		USF21	USF22	USF23	USF24	UNITS
Maximum recurrent peak reverse voltage	V_{RRM}	50	100	150	200	V
Maximum RMS voltage	V_{RMS}	35	70	105	140	V
Maximum DC blocking voltage	V_{DC}	50	100	150	200	V
Maximum average forward rectified current 9.5mm lead length, @ $T_A=75^\circ\text{C}$	$I_{F(AV)}$	2.0				A
Peak forward surge current 8.3ms single half-sine-wave superimposed on rated load @ $T_J=125^\circ\text{C}$	I_{FSM}	75.0				A
Maximum instantaneous forward voltage @ 2.0A	V_F	0.92				V
Maximum reverse current @ $T_A=25^\circ\text{C}$ at rated DC blocking voltage @ $T_A=100^\circ\text{C}$	I_R	10.0 350.0				μA
Maximum reverse recovery time (Note1)	t_{rr}	20				ns
Typical junction capacitance (Note2)	C_J	15				pF
Typical thermal resistance (Note3)	$R_{\theta JA}$	40				$^\circ\text{C/W}$
Operating junction temperature range	T_J	- 55 ----- + 150				$^\circ\text{C}$
Storage temperature range	T_{STG}	- 55 ----- + 150				$^\circ\text{C}$


NOTE: 1. Measured with $I_F=0.5\text{A}$, $I_R=1\text{A}$, $t_{rr}=0.25\text{A}$.

2. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.


3. Thermal resistance from junction to ambient.

www.galaxycn.com

FIG.1 -- TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTIC



NOTES: 1. RISE TIME = 7ns MAX. INPUT IMPEDANCE = $1M\Omega$, 22pF.
2. RISE TIME = 10ns MAX. SOURCE IMPEDANCE = 50Ω .



SET TIME BASE FOR 10/20 ns/cm

FIG.2 -- TYPICAL FORWARD CHARACTERISTIC

INSTANTANEOUS FORWARD
CURRENT, AMPERES




FIG.3 -- FORWARD DERATING CURVE

AVERAGE FORWARD CURRENT
AMPERES




FIG.4 -- TYPICAL JUNCTION CAPACITANCE

JUNCTION CAPACITANCE, pF




FIG.5 -- PEAK FORWARD SURGE CURRENT

PEAK FORWARD SURGE
CURRENT, AMPERES




FIG.6 -- TYPICAL REVERSE CHARACTERISTICS

INSTANTANEOUS REVERSE
CURRENT, MICROAMPERES

