




# SID100N12

## NPT IGBT Modules



Dimensions in mm (1mm = 0.0394")



### Absolute Maximum Ratings

$T_c = 25^\circ\text{C}$ , unless otherwise specified

Symbol	Conditions	Values	Units
<b>IGBT</b>			
$V_{CES}$		1200	V
$I_C$	$T_c = 25(80)^\circ\text{C}$	100(90)	A
$I_{CRM}$	$T_c = 25(80)^\circ\text{C}$ , $t_P = 1\text{ms}$	200(180)	A
$V_{GES}$		$\pm 20$	V
$T_{Vj}, (T_{stg})$	$T_{OPERATION} \leq T_{stg}$	$-40 \dots +150(125)$	$^\circ\text{C}$
$V_{isol}$	AC, 1min	2500	V
<b>Inverse Diode</b>			
$I_F = -I_C$	$T_c = 25(80)^\circ\text{C}$	95(65)	A
$I_{FRM}$	$T_c = 25(80)^\circ\text{C}$ , $t_P = 1\text{ms}$	200(180)	A
$I_{FSM}$	$t_P = 10\text{ms}$ ; sin.; $T_j = 150^\circ\text{C}$	720	A
<b>Freewheeling diode</b>			
$I_F = -I_C$	$T_c = 25(80)^\circ\text{C}$	130(90)	A
$I_{FRM}$	$T_c = 25(80)^\circ\text{C}$ , $t_P = 1\text{ms}$	200(180)	A
$I_{FSM}$	$t_P = 10\text{ms}$ ; sin.; $T_j = 150^\circ\text{C}$	1100	A

# SID100N12

## NPT IGBT Modules

### Characteristics

$T_c = 25^\circ\text{C}$ , unless otherwise specified

Symbol	Conditions	min.	typ.	max.	Units
<b>IGBT</b>					
$V_{GE(th)}$	$V_{GE} = V_{CE}, I_c = 2\text{mA}$	4.5	5.5	6.5	V
$I_{CES}$	$V_{GE} = 0; V_{CE} = V_{CES}; T_j = 25(125)^\circ\text{C}$		0.1	0.3	mA
$V_{CE(TO)}$	$T_j = 25(125)^\circ\text{C}$		1.4(1.6)	1.6(1.8)	V
$r_{CE}$	$V_{GE} = 15\text{V}, T_j = 25(125)^\circ\text{C}$		14.6(20)	18.6(25.3)	$\text{m}\Omega$
$V_{CE(sat)}$	$I_c = 75\text{A}; V_{GE} = 15\text{V}; \text{chip level}$		2.5(3.1)	3(3.7)	V
$C_{ies}$	under following conditions		5	6.6	
$C_{oes}$	$V_{GE} = 0, V_{CE} = 25\text{V}, f = 1\text{MHz}$		0.72	0.9	nF
$C_{res}$			0.38	0.5	
$L_{CE}$				30	nH
$R_{CC+EE}$	res., terminal-chip $T_c = 25(125)^\circ\text{C}$		0.75(1)		$\text{m}\Omega$
$t_{d(on)}$	under following conditions: $V_{CC} = 600\text{V}, I_c = 75\text{A}$		30	60	ns
$t_r$	$R_{Gon} = R_{Goff} = 15\ \Omega, T_j = 125^\circ\text{C}$		70	140	ns
$t_{d(off)}$	$V_{GE} = \pm 15\text{V}$		450	600	ns
$t_f$			70	90	ns
$E_{on}(E_{off})$			10(8)		mJ
<b>Inverse Diode</b> under following conditions:					
$V_F = V_{EC}$	$I_F = 75\text{A}; V_{GE} = 0\text{V}; T_j = 25(125)^\circ\text{C}$		2(1.8)	2.5	V
$V_{(TO)}$	$T_j = 125^\circ\text{C}$			1.2	V
$r_T$	$T_j = 125^\circ\text{C}$		12	15	$\text{m}\Omega$
$I_{RRM}$	$I_F = 75\text{A}; T_j = 25(125)^\circ\text{C}$		27(40)		A
$Q_{rr}$	$di/dt = 800\text{A}/\mu\text{s}$		3(10)		$\mu\text{C}$
$E_{rr}$	$V_{GE} = V$				mJ
<b>FWD</b> under following conditions:					
$V_F = V_{EC}$	$I_F = 75\text{A}; V_{GE} = 0\text{V}; T_j = 25(125)^\circ\text{C}$		1.85(1.6)	2.2	V
$V_{(TO)}$	$T_j = 125^\circ\text{C}$			1.2	V
$r_T$	$T_j = 125^\circ\text{C}$		9	11	$\text{m}\Omega$
$I_{RRM}$	$I_F = 75\text{A}; T_j = 25^\circ\text{C}$		30(45)		A
$Q_{rr}$	$di/dt = \text{A}/\mu\text{s}$		3.5(11)		$\mu\text{C}$
$E_{rr}$	$V_{GE} = V$				mJ
<b>Thermal Characteristics</b>					
$R_{th(j-c)}$	per IGBT			0.18	K/W
$R_{th(j-c)D}$	per Inverse Diode			0.5	K/W
$R_{th(j-c)FD}$	per FWD			0.36	K/W
$R_{th(c-s)}$	per module			0.05	K/W
<b>Mechanical Data</b>					
$M_s$	to heatsink M6	3		5	Nm
$M_t$	to terminals M5	2.5		5	Nm
$w$				160	g