

### FAST RECOVERY RECTIFIER

VOLTAGE RANGE: 100 --- 1000 V

CURRENT: 1.5 A


#### FEATURES

- ◇ Low cost
- ◇ Diffused junction
- ◇ Low leakage
- ◇ Low forward voltage drop
- ◇ High current capability
- ◇ Easily cleaned with Freon, Alcohol, Isopropanol and similar solvents
- ◇ The plastic material carries U/L recognition 94V-0

#### MECHANICAL DATA

- ◇ Case: JEDEC DO-15, molded plastic
- ◇ Terminals: Axial lead, solderable per MIL-STD-202, Method 208
- ◇ Polarity: Color band denotes cathode
- ◇ Weight: 0.014 ounces, 0.39 grams
- ◇ Mounting position: Any

#### DO - 15



#### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate by 20%.

|                                                                                                                     |                 | BYV<br>12     | BYV<br>13 | BYV<br>14 | BYV<br>15 | BYV<br>16 | UNITS              |
|---------------------------------------------------------------------------------------------------------------------|-----------------|---------------|-----------|-----------|-----------|-----------|--------------------|
| Maximum recurrent peak reverse voltage                                                                              | $V_{RRM}$       | 100           | 400       | 600       | 800       | 1000      | V                  |
| Maximum RMS voltage                                                                                                 | $V_{RMS}$       | 70            | 280       | 420       | 560       | 700       | V                  |
| Maximum DC blocking voltage                                                                                         | $V_{DC}$        | 100           | 400       | 600       | 800       | 1000      | V                  |
| Maximum average forward rectified current<br>9.5mm lead length, @ $T_A = 75^\circ\text{C}$                          | $I_{F(AV)}$     | 1.5           |           |           |           |           | A                  |
| Peak forward surge current<br>8.3ms single half-sine-wave<br>superimposed on rated load @ $T_J = 125^\circ\text{C}$ | $I_{FSM}$       | 60.0          |           |           |           |           | A                  |
| Maximum instantaneous forward voltage<br>@ 1.5 A                                                                    | $V_F$           | 1.3           |           |           |           |           | V                  |
| Maximum reverse current @ $T_A = 25^\circ\text{C}$<br>at rated DC blocking voltage @ $T_A = 100^\circ\text{C}$      | $I_R$           | 5.0<br>100.0  |           |           |           |           | $\mu\text{A}$      |
| Maximum reverse recovery time (Note1)                                                                               | $t_{rr}$        | 300           |           |           |           |           | ns                 |
| Typical junction capacitance (Note2)                                                                                | $C_J$           | 18            |           |           |           |           | pF                 |
| Typical thermal resistance (Note3)                                                                                  | $R_{\theta JA}$ | 45            |           |           |           |           | $^\circ\text{C/W}$ |
| Operating junction temperature range                                                                                | $T_J$           | - 55 --- +150 |           |           |           |           | $^\circ\text{C}$   |
| Storage temperature range                                                                                           | $T_{STG}$       | - 55 --- +150 |           |           |           |           | $^\circ\text{C}$   |


NOTE:1. Measured with  $I_F = 0.5\text{A}$ ,  $I_R = 1\text{A}$ ,  $t_{rr} = 0.25\text{A}$ .

2. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.


3. Thermal resistance from junction to ambient.

www.galaxycn.com

**FIG.1 – REVERSE RECOVERY TIME CHARACTERISTIC AND TEST CIRCUIT DIAGRAM**




NOTES: 1. RISE TIME = 7ns MAX. INPUT IMPEDANCE = 1MΩ, 22PF  
2. RISE TIME = 10ns MAX. SOURCE IMPEDANCE = 50Ω



**FIG.2 – TYPICAL FORWARD CHARACTERISTIC**


INSTANTANEOUS FORWARD CURRENT  
AMPERES



INSTANTANEOUS FORWARD VOLTAGE, VOLTS

**FIG.3– FORWARD DERATING CURRENT**


AVERAGE FORWARD RECTIFIED  
CURRENT, AMPERES



AMBIENT TEMPERATURE, °C

**FIG.4– PEAK FORWARD SURGE CURRENT**


PEAK FORWARD SURGE CURRENT  
AMPERES



NUMBER OF CYCLES AT 60Hz

**FIG.7 – TYPICAL JUNCTION CAPACITANCE**

JUNCTION CAPACITANCE, pF



REVERSE VOLTAGE, VOLTS